




	POWER DISTRIBUTION UNIT PR-3M-3G/W (3 OUTLETS) 2.8 m	POWER DISTRIBUTION UNIT PR-1.5M-4G/B (4 OUTLETS) 1.3 m	ACCESS POINT 4G LTE +ROUTER ARCHER-MR200 2.4 GHz, 5 GHz 433 Mbps + 300 Mbps TP-LINK
			
	3.86 EUR 3.86 EUR	3.71 EUR 3.71 EUR	86.09 EUR 86.09 EUR
Rated voltage	220 ... 240 V AC / 50 Hz	220 ... 240 V AC / 50 Hz	...
Frequency range	2.4 GHz , 5 GHz
Total maximal current	10 A	10 A	...
Maximal total load	2500 W	2500 W	...
Number of outlets	3 grounded outlets 10A/250V CEE 7/5	4 grounded outlets 10A/250V CEE 7/5	...
Fuse	—	—	...
Switch	—	—	...
Antenna type	3 x WiFi - built-in , 2 x 4G LTE
Wire gauge	3 x 1.5 mm ²	3 x 1.5 mm ²	...
Length of the cable	2.8 m	1.3 m	...
Housing	Plastic	Plastic	...
Standards	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3/3u
Color	White	Black	...
Baud rates	• 5 GHz : 433 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 150 Mbps
Modulation type	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM
LAN ports	• 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN

Receiver sensitivity	5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -67dBm • 11ac HT40: -64dBm • 11ac HT80: -60dBm • 11n HT20: -71dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -76dBm • 11n HT20: -73dBm • 11n HT40: -67dBm
LTE	✓
QSS	✓
WDS	✓
Power supply	12 V DC / 1 A (power adapter included)
Operation temp	0 °C ... 40 °C
Permissible relative humidity	95 % (non-condensing)
Main features	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button
Weight	0.39 kg	0.26 kg	0.26 kg
Dimensions	154 x 54 x 39 mm	196 x 54 x 39 mm	202 x 163 x 34 mm
Manufacturer / Brand	TP-LINK
Guarantee	2 years	2 years	3 years