



	ACCESS CONTROLLER WITH FACE RECOGNITION + READER ATLO-FR-601	ROUTER RUT301 Teltonika
		
	48.34 EUR 48.34 EUR	61.63 EUR 61.63 EUR
LAN ports	...	4 x 10 / 100 Mbps
Face recognition distance	0.5 m ... 1 m (max 1000 faces in the database)	...
WAN interface	...	1 x 10 / 100 Mbps
RFID proximity reader built-in	Unique EM 125kHz - Number of supported proximity cards : 10 000	...
Fingerprint reader built-in	Memory of 600 fingerprint patterns	...
LED indicators	...	Power, WAN, LAN
Range of IR illumination	5 m	...
Port USB	...	USB 2.0
White light LED illuminator range	—	...
DHCP server	...	✓
Video output	—	...
Wiegand interface	✓	...
DDNS	...	Support > 25
RS-485 interface	—	...
Alarm inputs / outputs	0 / 1 - Relay output	...
Protections	...	<ul style="list-style-type: none"> • IEEE 802.1x and Radius Authentication • MAC addresses filtering • Firewall • Support DDOS, SYN, SSH, HTTP/HTTPS defence • White list / Black list
Management interface	...	Web browser, Teltonika RMS application
Default IP address	...	192.168.1.1
Operating system	...	RutOS (Linux OS based)
Firmware update	...	✓

Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera • Identification modes : Face recognition, Fingerprint, Proximity identifier Unique EM 125kHz, Any combination of the above • Wiegand 26 • LEDs and buzzer • Buzzer for acoustic signaling of some system events 	...
Housing	Aluminum + Tempered glass, Vandal-proof	...
Color	Silver + Black	...
"Index of Protection"	IP65	...
Operation temp	-40 °C ... 60 °C	...




Main features	...	<ul style="list-style-type: none"> • Compliance with the Modbus, DLMS, DNP3, OPC UA protocol • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Static / dynamic routing • Support for VoIP technology, • View topology and network status • WMM support (QoS mechanism of the 802.11e standard) • DHCP Relay support • Load balance • VLAN support • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN • Compliance with the MQTT protocol • SNMP v1/v2/v3/Trap • Support for IoT (Internet of Things) systems, • Configuration using the Teltonika RMS application • Communication interface - Port USB 2.0 - possibility to connect external HDD, flash drive, additional modem, printer, USB-serial adapter • 2 digital inputs / outputs - ability to set certain I/O conditions to initiate event, • RESET button • Durable aluminum housing • Shock-proof • Industrial wide temperature design. • 4-pin industrial power socket, • Wide range of supported supply voltages • "Index of Protection" : IP30 • Ethernet cable included
Certificates	...	CE, UKCA, FCC, WEEE
Power supply	12 V DC	<ul style="list-style-type: none"> • 9 ... 30 V DC • 9 V DC / 1 A (power adapter included)
Power consumption	<ul style="list-style-type: none"> ≤ 3.6 W (operation) ≤ 2.2 W (standby) 	≤ 3.8 W



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	...	-40 °C ... 75 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.38 kg	0.23 kg
Dimensions	170 x 70 x 24 mm	100 x 90 x 30 mm
Manufacturer / Brand	ATLO	Teltonika
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00