








	SWITCH TL-SG3424 24-PORT + SFP TP-LINK	3 PCS SET ACCESS POINT + ROUTER MAXI8-3 Wi-Fi 6 2.4 GHz, 5 GHz DAHUA	THERMALLY CONDUCTIVE ADHESIVE TERM-GLUE/120 TUBE 120 g AG THERMOPASTY	FURNITURE POWER DISTRIBUTION UNIT FS-18 (3 OUTLETS) 1.8 m Virene	RFID PROXIMITY CARD ATLO-D194	HIGH POE POWER ADAPTER TAM01GT01GT-75 - 75 W DAHUA	TV OR MONITOR MOUNT BRATECK-PLB-6N
							
	198.84 CHF 198.84 CHF	187.00 CHF 187.00 CHF	20.58 CHF 20.58 CHF	25.53 CHF 25.53 CHF	0.63 CHF 0.63 CHF	51.06 CHF 51.06 CHF	15.89 CHF 15.89 CHF
Package	Tube 120 g
Rated voltage	230 V AC / 50 Hz
Total maximal current	16 A
In package	...	3 pcs
Standard
Maximal total load	3680 W
Input voltage	100 ... 240 V AC	...
Compatibility	ISO/IEC 14443A
Possibility of programming the serial number (ID)	---
Frequency range	...	2.4 GHz, 5 GHz
Output voltage	53 V DC	...
Ability to write to internal memory	---
Number of outlets	3 grounded outlets 16A/250V CEE 7/5, E type
Maximal output current	1.42 A	...
Serial Number overprint	---
Fuse	---
Number of inputs	1 pcs RJ-45	...
Switch	---
Mounting standard	VESA 75, 100, 150, 200, 200x100, 300, 400, 400x200
Wire gauge	3 x 1.5 mm ²
Length of the cable	1.8 m
Screen size range	26 " ... 47 "
Antenna type
Connector
Bearing capacity	75 kg
Distance from mounting surface	77 mm
LED indicators	Power, PoE	...
Tilt adjustment	-15 ° ... 15 °
Housing	Plastic + Aluminum
"Index of Protection"	IP20
Standards	High PoE - 75 W	...
Supported data rates
Color	White	Black + Silver	Black
Output power	75 W	...
Baud rates	...	574 Mbps + 1201 Mbps
Protections	...	WPA2
LAN ports	Switch is managed via a web browser, command line interface and SNMP, RMON protocols • 24 x RJ45, • 4 x port SFP - Uplink, • 1 x RJ45 - Console	3 x 10/100/1000 Mbps
Management	✓
Transmission speed	• 10 / 100 / 1000 Mbps - 24 LAN ports, • 100 / 1000 Mbps - 4 SFP ports
Power consumption	...	≤ 12 W
Jumbo Frame	10240 B
MAC addresses table	8k
Operation temp	...	-10 °C ... 55 °C	-30 °C ... 65 °C	...
Permissible relative humidity	...	5 % ... 95 %

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> Switch is managed via a web browser, command line interface and SNMP, RMON protocols CoS/DSCP priority based on IEEE 802.1p standard Queue scheduling: SP, WRR, SP+WRR Port/flow-based rate limiting IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs IGMP Snooping V1/V2/V3 Spanning Tree STP/RSTP/MSTP BPDU Filtering/Guard TC / Root Protect Loop back detection Data Flow Control (802.3x) IP-MAC-Port-VID Binding Access Control List - L2/L4 ACL package filtering based on source and destination MAC addresses IEEE 802.1x and Radius Authentication Support DoS defence Port Security IPv6 compliance SSL, SSH 	<ul style="list-style-type: none"> Support for Mesh technology, Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV Easy and uniform management system for many devices - WiLynk application Intuitive installation and configuration of many advanced functions 		<ul style="list-style-type: none"> Fixing in the opening of the table top $\varnothing 82$ mm PDU pulled out from the table top Outlets protected with a protection shutter 	Range : ~ 10 cm ,	Meets the requirements of DoE level VI	
LED diodes	Power, Link/Act, System, 1000 Mbps Console
Certificates	CE
Power supply	100 ... 240 V AC	12 V DC / 1.5 A (power adapter included)
Weight	3.02 kg	0.23 kg	...	0.67 kg	0.005 kg	0.48 kg	3.11 kg
Dimensions	440 x 220 x 44 mm, RACK 19", 1U	95 x 95 x 73 mm	...	$\varnothing 106$ x 284 mm	86 x 54 x 0.8 mm	210 x 75 x 38 mm	516 x 508 x 77 mm
Manufacturer / Brand	TP-LINK	DAHUA	AG TERMOPASTY	Virone	ATLO	DAHUA	...
Guarantee	5 years	2 years	2 years	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00