



	FLUSH BOX PK-60F/EPN Elektro-Plast	ACCESS CONTROL PANEL ACCO-NT2 SATEL
		
	1.21 AUD 1.21 AUD	608.31 AUD 608.31 AUD
Number of sections	1	...
"Index of Protection"	—	...
Inputs	...	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Outputs	...	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264
Material	Plastic	...
Color	Brick red	...
Communication	...	<ul style="list-style-type: none"> • 2 x RS-485 • Expander bus - up to 32 expander modules
Montage hole diameter	Ø 68 mm	...
Events memory	...	<ul style="list-style-type: none"> • Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module
Users + admins	...	<ul style="list-style-type: none"> • 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Output load	...	<ul style="list-style-type: none"> • OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC

Main features	<ul style="list-style-type: none"> • Flush-mounted, deep, for hollow walls • 2 special screws with holders to fastening to the wall - included 	<ul style="list-style-type: none"> • Support for up to 255 access control modules • Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition) • Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway) • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses
Power supply	...	12 V DC / 140 mA (max)
Battery backup support	...	—
Operation temp	...	-10 °C ... 55 °C
Permissible relative humidity	...	93 % (non-condensing)
Weight	0.026 kg	0.096 kg
Dimensions	Ø 60 x 61 mm - Internal dimensions Ø 72 x 62 mm - External dimensions	151 x 69 x 17 mm
Manufacturer / Brand	Elektro-Plast	SATEL
Guarantee	2 years	2 years