







	<a href="#">SPEAKER CABLE HI-FI/2X1.0</a>	<a href="#">RFID PROXIMITY CARD MFC-2 ROGER</a>	<a href="#">END CLAMP PV-KK/35-50/S FOR SOLAR PANELS 35 mm</a>	<a href="#">MECHANICAL TIMER OR PRE-443 ORNO</a>	<a href="#">CABLE OUTLET DPK1.01/11-SIMON54</a>	<a href="#">FLUSH BOX 4-GANG P-4X60-D SIMET</a>
						
	0.84 AUD 0.84 AUD	3.16 AUD 3.16 AUD	0.69 AUD 0.69 AUD	8.95 AUD 8.95 AUD	8.54 AUD 8.54 AUD	12.51 AUD 12.51 AUD
Device type	...	...	...	Mechanical timer	...	...
Number of sections	...	...	...	...	...	4
Maximal current	...	...	...	16 A	...	...
Support	...	...	...	...	Simon 54 product series, for Nature, Premium frames	...
Height	...	...	35 mm	...	...	...
Standard	...	13.56 MHz S50, 13.56 MHz S50 Classic	...	...	...	...
Maximal load	...	...	...	3680 W	...	...
Number of modules	...	...	...	...	1	...
Hole diameter	...	...	9 mm	...	...	...
mounting screw	...	...	—	...	...	...
In section	<b>100 m . Price for 1m when buying a whole roll</b>	...	...	...	...	...
Possibility of programming the serial number (ID)	...	—	...	...	...	...
Timing range	...	...	...	15 minutes ... 24 hours	...	...
Ability to write to internal memory	...	✓	...	...	...	...
The maximum countdown time	...	...	...	24 hours	...	...
Serial Number overprint	...	✓	...	...	...	...
Inner conductor	2 x Ø 1.0 mm Cu-OFC Stranded wire	...	...	...	...	...
Security class	...	...	...	IP20	...	...
Outer coating	PVC	...	...	...	...	...
Coating color	Colorless	...	...	...	...	...
Housing	...	...	...	Plastic	Non-halogen plastic, PC	...
Socket type	...	...	...	2P+Z, E type	...	...
Power supply	...	...	...	230 V AC, 50 Hz	...	...
Main features	...	<ul style="list-style-type: none"> <li>• ROM size: 1 kB</li> <li>• Data retention up to 10 years</li> <li>• Write endurance up to 100 000 cycles</li> </ul>	...	Time settings for switching electrical devices on and off	<ul style="list-style-type: none"> <li>• Cable diameter : 6.2 ... 14.5 mm</li> <li>• Claw or screw mounting</li> <li>• Installation in flush-mounted enclosures</li> <li>• Aesthetic and solid construction</li> </ul>	<ul style="list-style-type: none"> <li>• Flush-mounted for hollow walls</li> <li>• stiffened construction</li> <li>• flammability index : 960 °C</li> <li>• Class V0</li> <li>• 4 x 4 fixing points</li> <li>• 8 mounting screws, 4 special screws with holders to fastening to the wall, 6 cable partitions - included</li> </ul>
Material	...	...	Aluminum	...	...	halogen free and inflammable
"Index of Protection"	...	...	...	...	IP20	IP30
Color	...	...	Silver	...	White (RAL 9003)	Blue
Weight	...	0.006 kg	0.22 kg	0.15 kg	0.048 kg	0.17 kg
Mounting holes distance	...	...	...	...	...	60 mm
Dimensions	...	86 x 54 x 1 mm	50 x 38 x 28 mm	126 x 72 x 85 mm	<ul style="list-style-type: none"> <li>• 75 x 75 x 55 mm</li> <li>• 22 mm - mounting depth</li> </ul>	286 x 71 x 63 mm
Manufacturer / Brand	...	ROGER	...	ORNO	KONTAKT Simon	SIMET
Guarantee	2 years	3 years	2 years	2 years	6 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00