



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H52V21-36W - 8.3 Mpx 4K UHD 3.6 mm</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1400TL-0280B - 3.7 Mpx 2.8 mm DAHUA</a>
		
	36.92 EUR 36.92 EUR	79.33 EUR 79.33 EUR
Standard	AHD, HD-CVI, HD-TVI, PAL	HD-CVI, HD-TVI, AHD, CVBS
Sensor	1/2.5 " Progressive Scan CMOS	1/2.7 " CMOS
Matrix size	8.3 Mpx	3.7 Mpx
Audio	...	—
Resolution	<ul style="list-style-type: none"> <li>• 3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI 12.5 fps, 15 fps,</li> <li>• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI 12.5 fps, 20 fps,</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 15 fps, 25 fps, 30 fps,</li> <li>• 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps,</li> <li>• 960 x 576 - 960H @ PAL</li> </ul>	<ul style="list-style-type: none"> <li>• AHD / HD-CVI / HD-TVI : 2560 x 1440 - 3.7 Mpx ,</li> <li>• HD-CVI : 1920 x 1080 - 1080p ,</li> <li>• CVBS 960 x 576 - 960H, PAL</li> </ul>
Range of IR illumination	20 m	30 m
IR illuminator power adjustment	Automatic	Automatic
Lens	3.6 mm	2.8 mm
View angle	<ul style="list-style-type: none"> <li>• 77 ° (manufacturer data)</li> <li>• 84 ° (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 97 ° (manufacturer data)</li> <li>• 94 ° (our tests result)</li> </ul>
S/N ratio	> 50 dB	...
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω
Vandal-proof	...	—

Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	✓	OSD menu available via DAHUA recorder
Power supply	12 V DC / 280 mA	12 V DC / 330 mA
Power consumption	≤ 3.3 W	≤ 4 W
Housing	Dome - Metal	Dome, Aluminum + Plastic
Color	White	White
"Index of Protection"	IP66	IP67
IK rating	—	...
Operation temp	-20 °C ... 50 °C	-40 °C ... 60 °C
Weight	0.28 kg	0.22 kg
Dimensions	Ø 93 x 77 mm	Ø 97 x 86 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...
Manufacturer / Brand	APTI	DAHUA
Guarantee	2 years	3 years