







	TV OR MONITOR MOUNT BRATECK-LPA52-466	POWER SUPPLY ADAPTER PSC-12010/PRO 12 V DC 1 A	IP CAMERA TC-C35WS SPEC:15/E/Y/M/H/2.8MM/V4.1 - 5 Mpx 2.8 mm TIANDY	ROUTER WIFI HR300 2.4 GHz 300 Mbps IMOU	TV OR MONITOR MOUNT AX-HAMMER	RFID PROXIMITY CARD ATLO-104N*P200
						
	25.33 AUD 25.33 AUD	11.87 AUD 11.87 AUD	465.80 AUD 465.80 AUD	18.56 AUD 18.56 AUD	44.65 AUD 44.65 AUD	97.61 AUD 97.61 AUD
Adapter type	...	Switching
Frequency range	2.4 GHz
Standard	IP
Output voltage	...	12 V DC
Maximal load	...	1 A
Antenna type	2 x Omnidirectional antenna - Integrated
Average active efficiency	...	83 %
In package	200 pcs The price for package
Output power	...	12 W
Standard	Unique EM 125kHz
Standards	IEEE 802.11 a/b/g/n
Power consumption at no-load	...	< 0.1 W
Compatibility	EM4100/4102
Baud rates	300 Mbps
Number of outputs	...	1 pcs
Possibility of programming the serial number (ID)	-
Ability to write to internal memory	-
Power connectors type	...	2.1/5.5 mm - Straight plug
Serial Number overprint	✓
Mounting standard	VESA : 75, 100, 200, 300, 300x200, 400x200, 400, 600x200, 600x400	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	...
LAN ports	3 x 10/100 Mbps LAN 1 x 10/100 Mbps WAN
Power voltage	...	100 ... 240 V AC
LED indicators	Status
Housing type	...	Plastic
Screen size range	37 " ... 70 "	23 " ... 70 "	...
Bearing capacity	40 kg	50 kg	...
DHCP server	✓
Firmware update	✓
Distance from mounting surface	53 ... 464 mm	83 ... 455 mm	...
Protections	WPA-PSK, WPA2-PSK
Management interface	Web browser
Transmitter power	max. 20 dBm
Resolution	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Tilt adjustment	-15 ° ... 5 °	0 ° ... 15 °	...
Sensor	1/2.7 " Progressive Scan CMOS
Horizontal rotation	-60 ° ... 60 °	-45 ° ... 45 °	...
Lens	2.8 mm
Rotation in the plane of the screen	-3 ° ... 3 °	-	...
View angle	104 °
Range of IR illumination	50 m
Main features	...	<ul style="list-style-type: none"> • Short-circuit protection • Overload protection • The device has very small dimensions • Length of the cables : 40 + 15 cm 	...	<ul style="list-style-type: none"> • Static / dynamic routing • Built-in 3-port switch • DMZ • UPnP • DHCP client list 	...	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A • Range : ~ 11 cm • The TK-4100 chip
Operation temp	...	0 °C ... 40 °C	...	-10 °C ... 40 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio input • Audio output • Bi-directional audio streaming support • Audio transmission via network • Compliance with the AAC standard
Permissible relative humidity	10 % ... 90 % (non-condensing)
Memory card slot	Micro SD card support up to 512GB
Image compression method	S+265 / H.265 / H.264
Alarm inputs / outputs	1 / 1
Main stream frame rate	<ul style="list-style-type: none"> • 25 fps @ 5 Mpx • 50 fps @ 2 Mpx
Interface	10/100 Base-TX (RJ-45)
WEB Server	Built-in
Max. number of on-line users	2
ONVIF	✓
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	192.168.1.2
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 433, 3000, 3001, 3002, 23002
Mobile client access ports	3000, 3001
PC client access ports	3000, 3001
Port ONVIF	80
Intelligent image analysis	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • double crossing the line • abandoned/missing object • illegal parking • people counting • detection of people gathering • heat map • detection of loitering in a given area • running • protective helmet detection • detection of persons on duty • video tampering



Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Corridor mode • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA 	12 V DC / 0.5 A (power adapter included)
Power consumption	≤ 8 W	≤ 3.2 W
Housing	Compact - Metal
Color	Black	...	White	...	Black	...
"Index of Protection"	...	IP67	IP67
Mechanical protection class	—
Operation temp	-40 °C ... 65 °C
Weight	4.72 kg	0.12 kg	0.51 kg	0.13 kg	4.8 kg	0.006 kg
Dimensions	655 x 420 x (53 ... 464) mm	57 x 40 x 26 mm	162 x 71 x 71 mm	152 x 150 x 125 mm	670 x 430 x (83 ... 455) mm	86 x 54 x 1 mm
Supported languages	Polish, English, Albanian, Arabic, French, Hebrew, Spanish, Dutch, Korean, Portuguese, German, Russian, Thai, Turkish, Ukrainian, Italian, Vietnamese
Manufacturer / Brand	BRATECK	...	TIANDY	IMOU	...	ATLO
Guarantee	2 years	2 years	3 years	2 years	2 years	2 years