



	<a href="#">SOFT START MODULE SF-1</a>	<a href="#">SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE</a>
		
	85.28 SEK 85.28 SEK	1302.78 SEK 1302.78 SEK
Number of control inputs	1	...
Number of power inputs	1	...
Connectors	...	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs cable terminal</li> <li>• 1 pcs BNC</li> </ul>
Number of power outputs	1	...
Voltage	230 V AC	...
LAN ports	...	1 pcs RJ45 100 Mbps
Maximal output power	1150 W	...
Protection type	5 A 5/20mm delayed fuse	...
Connectors type	3 x screw terminals max. 1.5 mm <sup>2</sup>	...
Montage hole diameter	3 mm	...
Mounting holes distance	52 x 47 mm	...
LAN+PoE port configuration description	...	<ul style="list-style-type: none"> <li>• xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+"-": 3, 6 pins) or ("+"-": 4, 5 pins; "+"-": 7, 8 pins)</li> <li>• xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W</li> </ul>
Transmission range	...	<ul style="list-style-type: none"> <li>&lt; 1000 m @ Coaxial cable</li> <li>&lt; 100 m @ xCOAX4-SW - Switch PoE</li> <li>&lt; 100 m @ xCOAX4-CAM - IP Camera</li> </ul>
LED indicators	...	<ul style="list-style-type: none"> <li>• PoE</li> <li>• LAN</li> <li>• Link</li> <li>• 10Mb</li> </ul>
Protections	...	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, BNC</li> <li>• Short-circuit - xCOAX4-SW</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Watchdog function - Coaxial cable</li> </ul>
Power supply	...	xCOAX4-SW : <ul style="list-style-type: none"> <li>• 10 ... 58 V DC - cable terminal</li> <li>• PoE 802.3af/at / PASSIVE</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>
Power consumption	...	1.35 W (total)
Housing	...	Plastic (PC)
"Index of Protection"	...	IP20
Operation temp	...	-25 °C ... 65 °C
Weight	0.04 kg	0.033 kg (single element)
Dimensions	60 x 55 x 28 mm	<ul style="list-style-type: none"> <li>• 73 x 52 x 20 mm - xCOAX4-SW</li> <li>• 73 x 52 x 20 mm - xCOAX4-CAM</li> </ul>
Manufacturer / Brand	...	ATTE
Guarantee	2 years	3 years