



	SWITCH POE CS4006-4ET-60 4-PORT DAHUA	AHD, HD-CVI, HD-TVI, CVBS CAMERA APTI- H83V31-2812W - 8.3 Mpx, 4K UHD 2.8 ... 12 mm
		
	159.88 CAD 159.88 CAD	109.13 CAD 109.13 CAD
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	1/2.8 " SONY Starvis™ Back- illuminated CMOS
Matrix size	...	8.3 Mpx
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 10/100 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink 	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 Mbps : 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports 	...
Maximal total power	60 W	...
MAC addresses table	8k	...
Management	✓	...
Operation modes	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6	...
LED diodes	Power, System, PoE, Link/Act	...

Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall 	...
Certificates	CE	...
Resolution	...	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD, 15 fps , 3840 x 2160 - 8.3 Mpx, 4K UHD @ HD-CVI / HD-TVI, 15 fps / 12.5 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps / 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD, 30 fps / 25 fps / 15 fps , 2560 x 1440 - 4 Mpx @ HD-TVI / HD-CVI, 30 fps / 25 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps , 960 x 576 - 960H @ CVBS
Range of IR illumination	...	30 m
IR illuminator power adjustment	...	Automatic



Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	...
Lens	...	2.8 ... 12 mm
View angle	...	<ul style="list-style-type: none"> • 87 ° ... 24 ° (manufacturer data) • 85 ° ... 34 ° (our tests result)
Operation temp	-10 °C ... 55 °C	...
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / CVBS - selectable by switch
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines
OSD menu	...	✓
Housing	Desktop, Metal	Dome - Metal
Color	...	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Power supply	53 V DC / 1.22 A (power adapter included)	12 V DC / 750 mA
Power consumption	max. 65 W	≤ 9 W
Operation temp	...	-10 °C ... 60 °C
Weight	0.29 kg	0.56 kg
Dimensions	130 x 85 x 26 mm	Ø 120 x 98 mm
Supported languages	...	English, Spanish, Portuguese
Manufacturer / Brand	DAHUA	APTI
Guarantee	3 years	2 years