




	RJ-45 PLUG INTERNAL SHIELD RJ45/WP-N/INF	HD-CVI, PAL, TCP/IP DVR BCS-CVR0801E-III 8 CHANNELS
		
	0.06 EUR 0.06 EUR	198.49 EUR 198.49 EUR
Application	RJ-45 modular plug internal shield	...
Material	Rubber	...
Color	Blue	...
Standard	...	HD-CVI, PAL, TCP/IP
Maximal total frame rate	...	<ul style="list-style-type: none"> • HD-CVI, PAL : 120 fps @ 1920 x 1080 px, 200 fps @ 1280 x 720 px, 200 fps @ 960 x 576 px, • IP : 50 fps @ 1080p
Recording speed adjustment	...	<ul style="list-style-type: none"> • HD-CVI, PAL 1 ... 15 fps @ 1920 x 1080 1 ... 25 fps @ 1280 x 720 1 ... 25 fps @ 960 x 576 • IP 1 ... 25 fps @ 1920 x 1080
Operation modes	...	<ul style="list-style-type: none"> • 8 x HD-CVI / PAL • 7 x HD-CVI / PAL + 1 x IP 1080p • 6 x HD-CVI / PAL + 2 x IP 1080p • 2 x IP 1080p
Video inputs	...	8 pcs BNC, HD-CVI / PAL
Video outputs	...	1 pcs HDMI 1 pcs VGA
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
Image compression method	...	H.264
Number of compression levels	...	4
Image records resolutions	...	1920 x 1080 1280 x 720 960 x 576 704 x 576 352 x 288

Recording modes	...	Manual, Motion Detection, Schedule
Supported hard drives	...	1 x 4 TB SATA
External storage devices backup	...	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records	...	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS • Windows Phone: Free application wDMSS Lite There are also paid versions of mobile applications: gDMSS Plus, iDMSS Plus, wDMSS plus
Alarm inputs / outputs	...	—
PTZ control	...	—
Motion Detection	...	Split the screen into zones 22 x 18 motion zones Very good sensitivity after motion detection records detected channels only
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	...	12 V DC / 2 A (power adapter included)
Weight	0.001 kg	0.58 kg
Dimensions	27 x 12 x 15 mm	211 x 205 x 43 mm

Supported languages	...	English, Polish
Country of origin	...	China
Guarantee	2 years	2 years
Manufacturer / Brand	...	BCS



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00