






	DISK ARRAY ESS1504C 24 TB DAHUA	QUAD SMART LED LIGHTING CONTROLLER ATLO-SW4-TUYA Wi-Fi, Tuya Smart	VALVE ACTUATOR ATLO- V1-TUYA Wi-Fi, Tuya Smart	POWER DISTRIBUTION UNIT ACAR-504/WF/RACK	CONNECTION BOX PU-4D
					
	715.85 EUR 715.85 EUR	19.88 EUR 19.88 EUR	17.43 EUR 17.43 EUR	36.67 EUR 36.67 EUR	5.74 EUR 5.74 EUR
Application	...	switching devices on/off	control of the ball valve
Rated voltage	230 V AC	...
Rated current	10 A (total)	...
Number of channels	...	4
Number of intakes	4 - Cable glands PG-9
Response time	< 25 ns	...
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Supported hard drives	4 x SATA - max. 24 TB (total)
Cable diameter	4 ... 8 mm
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Valve Size	1/4 ", 3/8 ", 1/2 ", 3/4 "
Maximal total load	...	4 x 150W W
Nominal stroke current	2.5 kA (L/N) - 8/20 μs	...
Total maximal current	...	4 x 2.5 A
Number of inputs	...	4
Number of outputs	...	4
Maximum stroke current	6.5 kA (L/N) - 8/20 μs	...
Leak current	< 0.5 mA	...
Connector type	...	screw terminals
Outputs	• 1 x eSATA - 3 Gb/s (DVR) • 1 x USB 3.0 B (computer)
Number of outlets	5 grounded outlets 10A/250V	...
Write transfer rate	64 MB/s
Opening/closing time	5 ... 10 s
Read speed	64 MB/s
Switch	two-way, with light indication	...
Torque	2.9 ... 5.9 Nm
Length of the cable	2.7 m	...
Power supply	100 V ... 240 V AC	100 ... 240 V AC, 50 / 60 Hz	12 V / 1 A (power adapter included)
Radio communication range	...	< 100 m (open area)
Power consumption	6.8 W (without HDD)
Wireless	...	• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	...	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Permissible relative humidity	10 % ... 90 %
Manufacturer / Brand	DAHUA

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	<ul style="list-style-type: none"> Local control by physical button , Tuya Smart : <ul style="list-style-type: none"> schedule, timer, Setting scenarios by different events, remote access, voice control, The ability to set the default status of the device after a power failure 	<ul style="list-style-type: none"> schedule, timer, Setting scenarios by different events, remote access, voice control Wi-Fi indicator Easy installation - the actuator is mounted on ball valves with a lever Possibility of manual change of the valve position Easy pairing function The actuator allows you to determine the operating status after a power failure in the device settings of the Tuya application. Available options: 1. "close" - close the valve, 2. "open" - open the valve, 3. "Restart Memory" - restore to the previous state Safe 12V DC power supply
"Index of Protection"	...	IP20	IP67
Housing	...	Plastic	Plastic, Waterproof	RACK 19", 1U, Plastic - non-flammable	...
Color	...	White	Black
Operation temp	0 °C ... 40 °C	-10 °C ... 40 °C
Weight	4.29 kg	0.03 kg	0.4 kg	0.59 kg	...
Dimensions	440 x 408 x 70 mm - RACK 19", 1.5U	43 x 39 x 22 mm	<ul style="list-style-type: none"> 105 x 70 x 107 mm 1.35 m (cable length) 	383 x 58 x 55 mm	100 x 100 x 37 mm
Guarantee	3 years	2 years	2 years	2 years	2 years