




	IP SPEED DOME CAMERA OUTDOOR SD2A500HB-GN-AW-PV-0400-S2 Wi-Fi - 5 Mpx 4 mm DAHUA	TV OR MONITOR MOUNT AX-ORION RED EAGLE	TV OR MONITOR MOUNT BRATECK-LPA78-446
			
	2444.68 NOK 2444.68 NOK	195.49 NOK 195.49 NOK	136.43 NOK 136.43 NOK
Standard	TCP/IP
Sensor	1/2.8 " STARVIS™ CMOS
Matrix size	5 Mpx
Mounting standard	...	VESA, 200 x 200, 300 x 200, 300 x 300, 400 x 200, 400 x 300, 400 x 400, 600 x 400	VESA : 75, 100, 100x150, 150x150, 200x100, 200, 300x200, 300, 400x200, 400x300, 400
Screen size range	...	37 " ... 70 "	37 " ... 70 "
Bearing capacity	...	40 kg	40 kg
Distance from mounting surface	...	33 mm	67 ... 355 mm
Resolution	2560 x 1920 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 - 720p
Lens	4 mm
Tilt adjustment	...	—	-15 ° ... 3 °
Horizontal rotation	...	—	-60 ° ... 60 °
View angle	• 80 ° (manufacturer data) • 77 ° (our tests result)
Optical zoom	—
Rotation in the plane of the screen	...	± 3 °	-3 ° ... 3 °
Digital zoom	—
Range of IR illumination	30 m
White light LED illuminator range	30 m
Video output	—
Rotation speed (manual control)	• 0.1 °/s ... 74 °/s (horizontal) • 0.1 °/s ... 36 °/s (vertical)
Preset rotation speed	max. 62 °/s (horizontal) max. 36 °/s (vertical)
Horizontal rotation range	0 ° ... 345 ° - Rotation of the head is limited by stops
Vertical rotation range	0 ° ... 80 °
RS-485 interface	—
Number of presets	300
Horizontal scan	—
Route settings	—
Image compression method	H.264B / H.265+ / H.264 / H.265 / MJPEG / H.264+
Alarm inputs / outputs	—
Main stream frame rate	• 20 fps - 5 Mpx • 25 fps - 4 Mpx
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)
Network interface	• Wi-Fi - 2.4 GHz IEEE 802.11 b/g/n, • 10/100 Base-T (RJ-45)
WEB Server	Built-in, NVR compliance
Max. number of on-line users	20
ONVIF	21.06

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support
Mobile phones support	Port 37777 <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.108
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, • D-WDR - Wide Dynamic Range • 2-DNR, 3-DNR - Digital Noise Reduction • Day/night mode • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Motion Detection • Configurable Privacy Zones • Active deterrence function - Light and sound alarm • IVS analysis : intrusion : crossing the line (tripwire)
Power supply	12 V DC / 1.5 A
Power consumption	≤ 11 W
Housing	Speed Dome, Plastic
Color	White	Black	Black
"Index of Protection"	IP66
Operation temp	-30 °C ... 55 °C
Weight	0.44 kg	1.34 kg	3.36 kg
Dimensions	Ø 111 x 141 mm (without bracket)	660 x 295 x 33 mm	440 x 420 x (67 ... 355) mm
Supported languages	English
Manufacturer / Brand	DAHUA	RED EAGLE	BRATECK
Guarantee	3 years	2 years	2 years