



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TH-I8-A-0360B-S6 - 1080p 3.6 mm DAHUA</a>	<a href="#">AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR IDS-7204HUHI-M1/S/A(C)/4A+4/1ALM 4 CHANNELS ACUSENSE Hikvision</a>
		
	846.07 SEK 846.07 SEK	2944.87 SEK 2944.87 SEK
Standard	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Sensor	Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Video inputs	...	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Resolution	1920 x 1080 - 1080p , 960 x 576 - 960H	...
Lens	3.6 mm	...
Video outputs	...	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
View angle	83 °	...
Audio inputs	...	4 pcs CINCH, Coaxial audio - Audio from cameras
Audio outputs	...	1 pcs CINCH
Range of IR illumination	80 m	...
IR illuminator power adjustment	Automatic	...
Image compression method	...	H.265+ / H.265 / H.264 / H.264+
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	• Microphone built-in • Audio support via coaxial cable - HD-CVI only	...
S/N ratio	> 65 dB	...
OSD menu	✓	...
Power consumption	≤ 4.9 W	...
Housing	Compact, Plastic + Metal	...
"Index of Protection"	IP67	...
Operation temp	-40 °C ... 60 °C	...

Image records resolutions	...	<ul style="list-style-type: none"> <li>• HD-TVI : 8.3 Mpx 4K UHD - 3840 x 2160 1 CH only , 8M-N - 1920 x 2160 2,3,4 CH only , 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720 ,</li> <li>• AHD : 5 Mpx - 2560 x 1944 , 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 ,</li> <li>• HD-CVI : 3.7 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720 ,</li> <li>• PAL : 960H - 960 x 576 ,</li> <li>• IP : max. 8 Mpx - 3840 x 2160</li> </ul>
Recording speed adjustment	...	<ul style="list-style-type: none"> <li>8 Mpx IP @ 1 ... 25 fps</li> <li>8 Mpx @ 1 ... 8 fps</li> <li>8M-N @ 1 ... 15 fps</li> <li>5 Mpx @ 1 ... 12 fps</li> <li>4 Mpx @ 1 ... 15 fps</li> <li>3 Mpx @ 1 ... 18 fps</li> <li>1080p @ 1 ... 25 fps</li> <li>720p @ 1 ... 25 fps</li> <li>960H @ 1 ... 25 fps</li> </ul> for each channel
Operation modes	...	4 x HD-TVI / AHD / HD-CVI / CVBS / IP + 4 x IP
Recording modes	...	Manual, Sensor, Motion detection, Schedule
Supported hard drives	...	1 x 10 TB SATA
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface	...	1 x RJ-45 - 10/100 Base-TX
Bitrate	...	32 ... 10240 kbps
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a> iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a>
Default IP address	...	DHCP or 192.168.1.64



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	554 RTSP, 8000
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>
Alarm inputs / outputs	...	4 / 1
PTZ control	...	<ul style="list-style-type: none"> <li>• Control compatible with coax HD-TVI Hikvision</li> <li>• RS-485 - PELCO-D/P</li> </ul>
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones
USB	...	2 x USB 2.0
Mouse support	...	✓
IR remote controller in the set	...	—
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 8</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• DVR from the AcuSense series</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, Deep Learning technology</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> </ul>
Power supply	12 V DC / 410 mA	12 V DC / 1.5 A (power adapter included)
Color	White + Black	Black
Weight	0.41 kg	1.19 kg
Dimensions	91 x 90 x 241 mm	315 x 250 x 45 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	DAHUA	Hikvision
SAP Code	...	300226972
Guarantee	3 years	3 years

