



| | POE SWITCH WITH BUFFERED POWER SUPPLY IPUPS-8-20-H 8-PORT ATTE | SWITCH POE GTX-CLM1-10-8G2G 8-PORT |
|-------------------------------|--|--|
| |  |  |
| | 338.34 EUR 338.34 EUR | 144.08 EUR 144.08 EUR |
| LAN ports | <ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-T - Uplink, • 8 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE | <ul style="list-style-type: none"> • 8 x RJ45 (2 x Hi-PoE + 6 x PoE (802.3af/at)), • 2 x RJ45 - Uplink |
| Management | — | ✓ |
| Default IP address | ... | 192.168.2.1 |
| Transmission speed | <ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port Uplink, • 10 / 100 Mbps : 8 x Port LAN & PoE | <ul style="list-style-type: none"> 10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE |
| Default admin user / password | ... | admin / admin |
| Maximal output power | <ul style="list-style-type: none"> • 40 W @ Passive PoE - LAN1 ... LAN8 ports, • 30 W @ PoE (802.3af/at) - LAN1 ... LAN8 ports | <ul style="list-style-type: none"> • 90 W / port Hi-PoE - 1, 2 ports • 30 W / port PoE - 3 ... 8 ports |
| Maximal total power | 60 W | 120 W |
| Operation modes | Standard : 100 m @ 10/100 Mb/s - LAN1 ... LAN8 ports | <ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps |
| LED diodes | AC, DC, CHARGING (battery charging), PoE, Gigabit Ethernet | PWR, PoE, Link/Act |
| Certificates | ... | CE, FCC, RoHS |
| Protections | ... | Overvoltage ± 4 kV |
| Housing | ... | Metal |
| Operation temp | ... | -10 °C ... 55 °C |

| | | |
|----------------------|---|---|
| Main features | <ul style="list-style-type: none"> • 4K UHD support • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • 2 x Place for battery : 12 V / 18 Ah • Place for recorder (NVR) • Battery charging current : 1 A / 2 A - (set with the JP1 jumper) • Battery - Protection against reverse polarity connection, Protection against deep discharge of the battery • Technical outputs of the OC type signaling loss of voltage at the PSU output (OUF) and loss of voltage in the 230V mains (ACF) • PSU thermal protection : 130 °C • Overload protection • LAN & PoE ports - Short-circuit protection, Overvoltage • TAMPER switch indicating open the cover • "Index of Protection" : IP20 | <ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Auto-learning and Auto-aging functions support for MAC addresses • QoS - mechanisms, which provide the high quality of transmission • MTBF (Mean Time Between Faults) : 50000 h |
| Power supply | 190 ... 260 V AC | 48 ... 57 V DC, Power adapter included |
| Weight | 4.40 kg | 0.45 kg |
| Dimensions | 455 x 405 x 150 mm | 185 x 95 x 27 mm |
| Manufacturer / Brand | ATTE | ... |
| Guarantee | 3 years | 2 years |