



	<a href="#">PLUG F/6.5*P100</a>	<a href="#">NVR NVR504-16B 16 CHANNELS UNIVIEW</a>
		
	14.34 EUR 14.34 EUR	685.01 EUR 685.01 EUR
Standard	...	TCP/IP
Supported resolutions	...	max. 16 Mpx - 4608 x 3472 px
In package	<b>100 pcs The price for package</b>	...
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Connector type	"F" Straight plug	...
Attachment of connector elements	Twisted-on	...
Shield fastening	Twisting-on	...
Wire mounting	—	...
Audio support	...	<ul style="list-style-type: none"> <li>• 16 Channels - Audio from cameras</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>
Application	Coaxial cable	...
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
Cable diameter	max. 6.5 ± 0.05 mm	...
Impedance	75 Ω	...
Material	Metal	...
Image compression method	...	Ultra 265 / H.265 / H.264
Bitrate	...	max. 320 Mbps
Main features	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Corrosion resistance</li> </ul>	...
Supported hard drives	...	4 x 8 TB SATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Records playback from max. 16 channels in the same time

Network interface	...	2 x RJ-45 10/100/1000 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Network protocols	...	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, RTSP, IEEE 802.1x, IPv6
ONVIF	...	✓
Default IP address	...	DHCP or 192.168.1.30
Default admin user / password	...	admin / 123456
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	80
RTSP URL	...	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
USB	...	2 x USB 2.0 1 x USB 3.0
Serial ports	...	RS-485
Alarm inputs / outputs	...	16 / 4
PTZ control	...	• PTZ Uniview cameras • RS-485 - PELCO-D/P and others
Motion Detection	...	✓
Intelligent image analysis	...	✓

Main features	...	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, abandoned/missing object, scene changing, people counting, crowd gathering estimation, objects tracking</li> <li>• Smoke and temperature detection, fire detection</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Intelligent recognition of the human figure and tracking the movement of a person</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• VIDEO signal loss alarm</li> <li>• ANR - Automatic Network</li> </ul> <p>Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</p>
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	—
Power supply	...	12 V DC / 5 A (power adapter included)
Power consumption	...	≤ 20 W (without HDD)
Operation temp	...	-10 °C ... 55 °C
Weight	0.005 kg	3.17 kg
Dimensions	Ø 11 mm x 20 mm	440 x 352 x 48 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	...	UNIVIEW
Guarantee	2 years	3 years