

	SWITCHING ADAPTER 24V/0.83A-TP MW POWER	NVR BCS-L-NVR3208-A-4K 32 CHANNELS + eSATA BCS Line
		
	6.31 CHF 6.31 CHF	1765.45 CHF 1765.45 CHF
Standard	...	TCP/IP
Adapter type	Switching	...
Supported resolutions	...	32 Mpx
Power voltage	90 ... 264 V AC	...
Video outputs	...	2 pcs HDMI 2 pcs VGA
Frequency range	47 ... 63 Hz	...
Audio support	...	32 Channels - Audio from cameras
Output voltage	24 V DC	...
Audio inputs	...	1 pcs CINCH
Output voltage tolerance	± 5 %	...
Audio outputs	...	1 pcs CINCH
Maximal load	0.83 A	...
Output power	19.92 W	...
Efficiency	85 %	...
Number of outputs	1 pcs	...
Image compression method	...	H.265+ / H.265 / H.264 / H.264+ / MJPEG
Protections	<ul style="list-style-type: none"> • Overload • Short-circuit • Overvoltage • Overheat 	...
Main features	Can be installed in a 60mm electrical box	...
Housing type	Aluminum	...
Supported hard drives	...	8 x 16 TB SATA + eSATA , Raid 0/1/5/6/10
"Index of Protection"	IP66	...
Recording modes	...	Manual, Sensor, Motion detection, Schedule
Operation temp	-20 °C ... 50 °C	...
Network protocols	...	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/8/9 channel synchronous playback

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Bitrate	...	max. 384 Mbps
Network interface	...	2 x RJ-45, 10/100/1000 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in
ONVIF	...	✓
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Serial ports	...	RS-485, RS-232
USB	...	2 pcs USB 2.0 2 pcs USB 3.0
Alarm inputs / outputs	...	16 / 8
PTZ control	...	IP Speed Dome Cameras
Motion Detection	...	✓
Intelligent image analysis	...	✓



Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, face detection • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Face recognition • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Support for up to 20 face databases, including 20 000 face images • In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity • Privacy zones • Cooperation with POS (Point of Sale) terminals <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles)
Mouse support	...	✓
IR remote controller in the set	...	✓
Power supply	...	230 V AC
Weight	0.11 kg	6.5 kg
Dimensions	57 x 48 x 25 mm	440 x 454 x 95 mm
Supported languages	...	Polish, English
Manufacturer / Brand	MW POWER	BCS Line
Guarantee	2 years	3 years