



	<a href="#">ACCESS CONTROLLER ASI1212F DAHUA</a>	<a href="#">VIDEO SEPARATOR D-SEP/HD-4</a>
		
	225.55 EUR 225.55 EUR	20.31 EUR 20.31 EUR
Cards support	13.56 MHz S50	...
Reading distance of prox-keys	1 ... 3 cm	...
Keyboard built-in	—	...
Autonomous operation	✓	...
Battery backup support	—	...
Input lines	3	...
Output lines	3	...
Identification time	< 1.5 s	...
Standard	...	<ul style="list-style-type: none"> <li>• AHD - 8 Mpx, 4K UHD</li> <li>• HD-CVI - 8 Mpx, 4K UHD</li> <li>• HD-TVI - 8 Mpx 4K UHD</li> <li>• CVBS - PAL / NTSC</li> </ul>
Device type	...	Passive
Number of inputs	...	4 pcs BNC socket
Communication	<ul style="list-style-type: none"> <li>• RS-485</li> <li>• Wiegand</li> <li>• LAN</li> </ul>	...
Number of outputs	...	4 pcs BNC socket
RS-485 interface	✓	...
Input impedance	...	75 Ω
RS-232 interface	—	...
Output impedance	...	75 Ω
Wiegand interface	✓	...
Opto-isolation between inputs and outputs	...	50 V DC
Network interface	10/100 Base-T	...
Galvanic separation between individual channels	...	> 2000 V
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
USB	—	...
Memory card slot	—	...

Internal memory	Support storage of 150 000 records	...
Attenuation	...	<ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.37 dB</li> <li>• 11 MHz @ 0.47 dB</li> <li>• 21 MHz @ 0.62 dB</li> <li>• 38 MHz @ 0.93 dB</li> <li>• 42 MHz @ 0.93 dB</li> <li>• 67.5 MHz @ 1.16 dB</li> </ul>
Bandwidth	...	200 MHz
Inputs protection	...	ESD, IEC 61000-4-2, $\pm 30$ kV contact, $\pm 30$ kV air EFT, IEC 61000-4-4, 40A (5/50ns) Lightning, IEC 61000-4-5, 30A ( $t_p=8/20\mu s$ )
Power supply	12 V DC / 1 A	—

Main features	<ul style="list-style-type: none"> <li>• Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen</li> <li>• Fingerprint reader built-in</li> <li>• Memory of 3000 fingerprint patterns</li> <li>• Possible connection of the external ASR series reader (read in/out door control)</li> <li>• Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above</li> <li>• Remote access verification</li> <li>• Tamper detection - removing from mounting surface</li> <li>• Support for door contact and exit button</li> <li>• Indication of forced entry and the lack of closing doors</li> <li>• 30000 indexed users</li> <li>• Possibility to configure access groups</li> <li>• 128 General Purpose Schedules</li> <li>• 128 time periods within single Schedule</li> <li>• Holiday Schedules</li> <li>• Anti-passback</li> <li>• Integration with an alarm system via in/out line</li> <li>• Remote programming from PC</li> </ul>	...
"Index of Protection"	—	...
Operation temp	-10 °C ... 45 °C	-20 °C ... 55 °C
Permissible relative humidity	5 ... 90 % (non-condensing)	...
Dimensions	115 x 115 x 32 mm	103 x 78 x 30 mm
Weight	0.22 kg	0.12 kg
Supported languages	English	...
Manufacturer / Brand	DAHUA	DELTA
Guarantee	3 years	3 years