




	<a href="#">MAINS ADAPTER WITH GROUNDING WS-PL/GS-UNI-3</a>	<a href="#">CEE-PLUG PCE-0246 400 V 32 A 4P 6H IP44 / IP54</a>	<a href="#">STRAIGHT PLUG LE-555234 230 V 32 A LEGRAND</a>
			
	11.88 DKK 11.88 DKK	37.46 DKK 37.46 DKK	64.94 DKK 64.94 DKK
Voltage	250 V AC	...	...
Rated voltage	...	400 V / 50 ... 60 Hz	230 V / 50 Hz
Max. current	10 A	...	...
Maximal current load	...	32 A	32 A
Number of poles	...	4P	...
Grounding	...	6h	✓
Electrical cable	...	max. 4 x 6 mm <sup>2</sup>	max. 3 x 6 mm <sup>2</sup>
Cable terminals	...	screw terminals	screw terminals
Plug type	...	CEE	CEE, 2P+Z
Contact material	...	CuZn	...
Maximum wire insulation diameter	...	20 mm	...
Main features	Color : White	...	<ul style="list-style-type: none"> <li>• Heat resistance : 850 °C ( 650 °C - housing )</li> <li>• IEC/EN 60309-1, IEC/EN 60309-2 compliance</li> <li>• Screw-free plug closure</li> <li>• Integrated cable gland</li> </ul>
Material	PVC	...	Plastic - Polyamide 6
"Index of Protection"	...	IP44 / IP54	IP44
Mechanical strength	...	...	IK09
Weight	...	0.2 kg	0.19 kg
Dimensions	55 x 55 x 46 mm	150 x 80 x 67 mm	180 x 78 x 68 mm
Color	...	Red	Gray + Blue
Manufacturer / Brand	...	PCE	LEGRAND
Guarantee	2 years	2 years	2 years