




	<a href="#">IP CAMERA BCS-L-TIP52FC-AI2 NightColor - 1080p 3.6 mm</a>	<a href="#">ACCESS POINT C52IG-5HAXD2HAXD-TC hAP ax<sup>2</sup>, Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1200 Mbps MIKROTIK</a>
		
	140.25 EUR 140.25 EUR	111.35 EUR 111.35 EUR
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Frequency range	...	2.4 GHz, 5 GHz ,
Scanning system	Progressive	...
Antenna type	...	2x2 MIMO - built-in • 4.5 dBi @ 2.4 GHz • 4 dBi @ 5 GHz
Resolution	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Lens	3.6 mm	...
View angle	• 88 ° (manufacturer data) • 85 ° (our tests result)	...
Range of IR illumination	—	...
Standards	...	IEEE 802.11 b/g/n/ax @ 2.4 GHz , IEEE 802.11 a/n/ac/ax @ 5 GHz , Wave2 support
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Baud rates	...	574 Mbps + 1200 Mbps
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
LAN ports	...	4 x 10 / 100 / 1000 Mbps LAN 1 x 10 / 100 / 1000 Mbps Uplink
Alarm inputs / outputs	1 / 1	...
Audio	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection	...
LED indicators	...	Power, User, 4 x Ethernet, WAN, PoE OUT
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network protocols	IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE IEEE 802.1x, SNMP	...
Receiver sensitivity	...	2.4 GHz : • 1M : -100 dBm • 11M : -94 dBm • 6M : -96 dBm • 54M : -80 dBm • MCS0 : -96 dBm • MCS7 : -75 dBm • MCS9 : -70 dBm • MCS11 : -67 dBm 5 GHz : • 6M : -96 dBm • 54M : -80 dBm • MCS0 : -96 dBm • MCS7 : -75 dBm • MCS9 : -70 dBm • MCS11 : -67 dBm
Max. number of on-line users	20	...
DHCP server	...	✓
ONVIF	20.06	...
Firmware update	...	✓
Protections	...	WPA3, Firewall
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">BCS Manager</a> • iOS (iPhone): Free application <a href="#">BCS Manager</a>	...
Operating system	...	MikroTik RouterOS
Management interface	...	Web browser
Default IP address	192.168.1.108	192.168.88.1
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Transmitter power	...	max. 24 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz
WEB Server	Built-in, NVR compliance	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...



Main features	...	<ul style="list-style-type: none"> <li>• Built-in 5-port switch</li> <li>• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li> <li>• 2x2 MIMO / Dual-chain @ 2.4 GHz, 5 GHz</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source</li> <li>• IPsec</li> <li>• Passive PoE - 1 x Input / Output ( port Internet/PoE IN/OUT )</li> <li>• Possible power supply via Passive PoE via eth1/Poe OUT port - 0.6 A, 16.8 W (max)</li> <li>• Mode button</li> <li>• RESET button</li> </ul>
Operation temp	...	-40 °C ... 50 °C
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• NightColor - colorful night mode</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable Privacy Zones</li> <li>• Motion Detection</li> <li>• Mirror - Mirror image</li> <li>• Heat map - the selection in the image by corresponding colors the areas with different traffic</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, abandoned/missing object, fast moving, illegal parking, detection of people gathering, loitering detection, face detection, people counting</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• ePoE,</li> <li>• 12 V DC / 320 mA</li> </ul>	<ul style="list-style-type: none"> <li>• 12 ... 28 V DC - 24 V DC / 1.2 A (power adapter included)</li> <li>• 18 ... 28 V DC - Passive PoE</li> </ul>
Power consumption	≤ 3.8 W	max. 27 W
Housing	Compact - Metal / Plastic	...
Color	White	...


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP67	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.95 kg	0.27 kg
Dimensions	244 x 79 x 76 mm	120 x 100 x 33 mm
Supported languages	Polish, English	...
Manufacturer / Brand	BCS	MikroTik
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00