





	TV OR MONITOR MOUNT BRATECK-LPA63-446	SMART GATE AND DOOR CONTROLLER SBW-02 Wi- Fi. SUPLA 12 ... 24 V AC/DC ZAMEL	POLE MOUNT BD-LP09	IP CAMERA IPC3635LB-ADZK-H - 5 Mpx 2.8 ... 12 mm - MOTOZOOM UNIVIEW
				
	17.59 GBP 17.59 GBP	51.91 GBP 51.91 GBP	14.00 GBP 14.00 GBP	250.13 GBP 250.13 GBP
Standard	TCP/IP
Support	...	SUPLA
Suitable for cameras	OMEGA-21P22-6	...
Application	...	swing gates, sliding gates, garage gates, doors
Sensor	1/2.7 " Progressive Scan CMOS
Matrix size	5 Mpx
Rated voltage	...	12 ... 24 V AC/DC
Pole diameters range	Ø 90 ... Ø 120 mm	...
Maximal total load	...	—
Material	Steel - powder painted	...
Total maximal current	...	3 A
Number of inputs	...	2
Number of outputs	...	2
Connector type	...	screw terminals
Mounting standard	VESA : 75, 100, 150x100, 150, 200x100, 200, 300x200, 300, 400x200, 400x300, 400
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Screen size range	32 " ... 70 "
Bearing capacity	40 kg
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Distance from mounting surface	62 ... 468 mm
Lens	2.8 ... 12 mm - Motozoom, AutoFocus
Tilt adjustment	-15 ° ... 5 °
View angle	96 ° ... 33 °
Horizontal rotation	-60 ° ... 60 °
Rotation in the plane of the screen	± 3 °
Range of IR illumination	40 m
RS-485 interface	—
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)

Main features	...	<ul style="list-style-type: none"> • Control from a Web browser, • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—
Operation temp	...	-20 °C ... 50 °C
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection
Main stream frame rate	25 fps @ 5 Mpx
Network interface	10/100 Base-TX (RJ-45)
WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Mobile phones support	...	<ul style="list-style-type: none"> • The SUPLA free application on Android • The SUPLA free application on iOS 	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Motion detection with human/vehicle silhouette recognition • Privacy zones - max. 4 • Tamper signaling • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 630 mA
Power consumption	≤ 7.5 W
Housing	...	Plastic	...	Dome - Metal
Color	Black	Green	White	White
"Index of Protection"	...	IP20	...	IP67
Vandal-proof	—
Operation temp	-30 °C ... 60 °C
Weight	4.44 kg	0.037 kg	0.92 kg	0.66 kg
Dimensions	455 x 420 x (62 ... 468) mm	47 x 47 x 20 mm	131 x 170 mm	Ø 129 x 110 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	BRATECK	ZAMEL	...	UNIVIEW
Guarantee	2 years	2 years	2 years	3 years