




| | MULTIPURPOSE WIRED DETECTOR XD-2-DG SATEL | WATER FLOOD DETECTOR OR-DC-629 ORNO |
|--|---|--|
| |  |  |
| | 103.00 PLN 103.00 PLN | 52.40 PLN 52.40 PLN |
| Support | Alarm control panel | ... |
| Detection | Opening the door or window, Vibrations, Water | Water |
| Environmental class EN 50130-5 | II | ... |
| Protection class (Grade) | 2 | ... |
| Sensitivity adjustment | — | — |
| Alarm signaling | LED indicator, Signal to control panel | Beep signal : 95 dB (low), > 110 dB (high) |
| Relay contacts rating (resistive load) | 40 mA / 24 V DC | ... |
| Power supply | 12 V DC / 14 mA (max) | 3 x 1.5V, type AAA/LR03 battery (not included) |
| Current consumption | ... | <ul style="list-style-type: none"> • < 40 mA (alarm) • 40 µA (Standby mode) |

| | | |
|----------------------|---|--|
| Main features | <ul style="list-style-type: none"> • Operation modes : <ul style="list-style-type: none"> - Magnetic detector - Opening the door or window - input for connecting a NC type wired detector - 1 Alarm output - Shock detector - Detection of shocks and vibrations associated with attempts to force a door or window - Range : 3 m - input for connecting a NC type wired detector - 1 Alarm output - Shock and magnetic detector - Detection of shocks and vibrations associated with attempts to force a door or window - Opening the door or window - input for connecting a NC type wired detector - 2 Alarm outputs <ul style="list-style-type: none"> - Water flood detector - The required FPX-1 probe is available separately - detecting the presence of water in spaces where there is a risk of leakage - 1 Alarm output • Tamper detection - opening the enclosure, removing from mounting surface • LED indication • Supply voltage control • 2 magnets included (for surface and flush mounting) • Compliance with EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-2-6 standards | <ul style="list-style-type: none"> • detecting the presence of water in spaces where there is a risk of leakage - Autonomous operation • Magnetic probe - on the cable • 2-level volume adjustment • Test button • Low battery level alarm |
| Color | Dark graphite | White |
| Operation temp | -10 °C ... 55 °C | -30 °C ... 60 °C |
| Weight | 0.023 kg | 0.08 kg |
| Dimensions | <ul style="list-style-type: none"> • 20 x 102 x 23 mm (detector) • Ø 10 x 28 mm (magnet) | <ul style="list-style-type: none"> • 122 x 46 x 18 mm • 1.2 m - Length of the cable |
| Manufacturer / Brand | SATEL | ORNO |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | |
|-----------|---------|---------|
| Guarantee | 2 years | 2 years |
|-----------|---------|---------|



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00