





	POWER SEPARATOR PFM790 DAHUA	ACCESS POINT +ROUTER ACB-AC Wi-Fi 5, 5 GHz, 2.4 GHz, 867 Mbps + 300 Mbps UBIQUITI	PROXIMITY READER MCT80M-BLE ROGER	SIGNAL INDICATOR MIE- TV-SAT/CORAB TV-SAT CORAB
				
	18.89 EUR 18.89 EUR	98.02 EUR 98.02 EUR	200.88 EUR 200.88 EUR	4.63 EUR 4.63 EUR
Output and input	F socket
Support	RACS 5 (Roger)	...
Number of inputs	1
Cards support	13.56 MHz S50	...
Number of outputs	1
Reading distance of prox-keys	max. 7 cm	...
Keyboard built-in	—	...
Frequency range	...	5 GHz , 2.4 GHz ,	...	950 ... 2150 MHz
Input voltage	12 V DC ± 20 %
Signal level	-40 ... -10 dBm
Autonomous operation	—	...
Doorbell button	✓	...
Output voltage	12 V DC ± 5 %
Light button	✓	...
Output current	max. 400 mA
Input socket type	2.1/5.5 mm socket
Powering from receiver	DC 13 V / 18 V
Tamper output	✓	...
Output socket type	2.1/5.5 mm plug
Backlighting meter indications	✓
Communication	RS-485	...
Current consumption	90 mA
Sound signaling	✓
Antenna type	...	2x2 MIMO - built-in • 4 dBi @ 2.4 GHz • 5 dBi @ 5 GHz
Impedance	75 Ω
Efficiency	85 % @ 400 mA
Standards	...	IEEE 802.11ac, Wi-Fi 5
Average current consumption	60 mA	...
Baud rates	...	867 Mbps @ 5 GHz + 300 Mbps @ 2.4 GHz
Protections	...	WPA2
"Index of Protection"	IP65	...
LAN ports	...	4 x 10/100/1000 Mbps
Transmitter power	...	22 dBm (max)
Power supply PoE	...	Ubiquiti Passive PoE

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	...	<ul style="list-style-type: none"> • 24 V DC / 830 mA - (power adapter included) • PoE 24 V - Port 1 	12 V DC	...
Power consumption	...	≤ 8.5 W
Main features	...	<ul style="list-style-type: none"> • PoE OUT 24 V - port WAN, (4, 5+; 7, 8-) • Wi-Fi 5 • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network 	<ul style="list-style-type: none"> • Mobile identification via telephone with NFC / Bluetooth • Tamper protection (detection of removing from mounting surface and enclosure opening) • LED indication • Beep signal 	...
Operation temp	-30 °C ... 60 °C	-10 °C ... 50 °C	-25 °C ... 60 °C	...
Permissible relative humidity	...	5 % ... 95 %	10 ... 95 % (non-condensing)	...
Weight	0.032 kg	0.28 kg	0.09 kg	0.08 kg
Dimensions	108 x 22 x 20 mm	89 x 90 x 89 mm	100 x 45 x 16 mm	112 x 62 x 45 mm
Manufacturer / Brand	DAHUA	UBIQUITI	ROGER	CORAB
Guarantee	3 years	2 years	3 years	2 years