



	VIDEO DOORPHONE KIT KTA02 DAHUA	ACCESS POINT MAP-2ND mAP, 2.4 GHz 300 Mbps MIKROTIK
		
	194.23 EUR 194.23 EUR	50.64 EUR 50.64 EUR
Frequency range	...	2.4 GHz
Processor	...	Qualcomm Atheros AR9531 650 MHz
Sensor	1.3 Mpx CMOS	...
Camera view angle	70 °	...
IR illuminator	Built-in Infra-Red illuminator enables night monitoring	...
proximity reader built-in	—	...
Video output	compatible with DAHUA analog video door-phone system	...
Antenna type	...	2 x 2 MIMO Omnidirectional antenna , Dual-chain - embedded 1.2 dBi
Audio inputs	1 - Microphone	...
Standards	...	IEEE 802.11 b/g/n
Baud rates	...	300 Mbps
Audio outputs	1 - Speaker	...
LAN ports	...	2 x 10 / 100 Mbps LAN
LED indicators	...	Power, Operation mode, WiFi, User, PoE OUT, 2 x Ethernet
"Index of Protection"	IP66 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	...
Receiver sensitivity	...	2.4 GHz : • 1M : -96 dBm • 11M : -89 dBm • 6M : -93 dBm • 54M : -74 dBm • MCS0 : -93 dBm • MCS7 : -71 dBm
Transmitter power	...	max. 22 dBm
DHCP server	...	✓
Firmware update	...	✓
Operating system	...	MikroTik RouterOS

Shield	7 " TFT-LCD color matrix	...
Resolution	1024 x 600	...
Management interface	...	Web browser, MikroTik application
Default IP address	...	192.168.88.1
Operation modes	...	<ul style="list-style-type: none"> • Access Point, • Station
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • Operation status LED indicator - green LED - power indicator • Doorbell button • Inputs : Exit button, Door status detection • Surface mount • Rain cover included • Touch control keys, • Operation status LED indicator - green LED - power indicator, • The maximum number of gate stations in the system : 2, • The maximum number of indoor panels in the system : 3, • Selecting the ringer melody, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Preview image from the door station with the possibility of turning on the sound and opening the gate, • 4-wire cable installation, • Communication : compatible with DAHUA analog video door-phone system • Surface mount, • In the kit : Bracket 	...
Power supply	<p>12 V DC / 1 A (powered by indoor monitor)</p> <p>12 V DC / 1 A - Monitor</p> <p>12 V DC / 2 A (power adapter included)</p>	<ul style="list-style-type: none"> • 8 ... 57 V DC - 24 V DC / 0.8 A (power adapter included) • 10 ... 57 V DC - Passive PoE, PoE (802.3af/at) • 5 V DC - Micro USB-B socket

Main features	...	<ul style="list-style-type: none"> • Dual-chain • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Built-in 2-port switch • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Port USB 2.0 - Possibility to connect 3G/4G modem, Power connector • PoE IN : PoE 802.3af/at / PASSIVE - port ETH1 • PoE OUT : Passive PoE - port ETH2 • Voltage control • Mode button • RESET button • USB A / micro USB B cable included
Power consumption	≤ 3 W Operation ≤ 1 W Standby ≤ 5 W Operation ≤ 2 W Standby	max. 5 W
Housing	Plastic (PC + ABS) Plastic (PC + ABS)	...
Color	Silver + Black White	...
Operation temp	-30 °C ... 60 °C -10 °C ... 55 °C	-20 °C ... 70 °C
Weight	0.14 kg 0.25 kg	0.068 kg
Dimensions	46 x 131 x 34 mm 183 x 134 x 18 mm	68 x 68 x 19 mm
Manufacturer / Brand	DAHUA	MikroTik
Guarantee	3 years	2 years