




	WIRELESS TRANSMISSION KIT 5.8 GHz CAM-ANALOG-2.0 TXRX SET	RJ-45 PLUG SHIELD RJ45/WP-C*P100	RJ-45 PLUG SHIELD RJ45/WP-G*P10
			
	1958.62 DKK 1958.62 DKK	25.15 DKK 25.15 DKK	3.18 DKK 3.18 DKK
In package	...	100 pcs The price for package	10 pcs The price for package
Application	...	RJ-45 modular plug shield	RJ-45 modular plug shield
Material	...	Rubber	Rubber
Video format	AHD / HD-CVI / HD-TVI / CVBS : max. 1080p
Color	...	Black	Green
Frequency range	5.725 ... 5.875 GHz
Number of channels	2
Transmitter power	25 mW, 14 dBm
Receiver sensitivity	-85 dBm
Antenna beam angle	45 °
Radio communication range (at open area)	max. 500 m
Modulation	FM
Audio frequency response	—
Connectors	BNC socket : 1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> • Real time transmission, with no delays nor loss of image quality • interference free transmission (industrial, 802.11, Bluetooth, radiotelephony, etc.) • High gain directional antennas providing stable operation
Proper operation conditions	<ul style="list-style-type: none"> • the kit (transmitter and receiver) supporting the same camera, has to be set to the same channel (switch set to the same number) • at the same location, each of used kits has to be set to different channel • the transmitter and receiver antennas should be visible to each other (no obstacles like building, walls, trees, etc. between them)

Maximal mast diameter	Ø 50 mm
Power supply	9 V ... 16 V DC
Current consumption	<ul style="list-style-type: none"> • ≤ 800 mA - Tx • ≤ 500 mA - Rx
Operation temp	-20 °C ... 55 °C
"Index of Protection"	IP66
Weight	<ul style="list-style-type: none"> • 0.38 kg - Tx • 0.48 kg - Rx
Dimensions	<ul style="list-style-type: none"> • 152 x 105 x 60 mm - Tx • 164 x 164 x 80 mm - Rx
Manufacturer / Brand	CAMSAT
Guarantee	2 years	2 years	2 years