



	<a href="#">PIR DETECTOR MD-10B7 AC 230V FOR LIGHTING CONTROL EL HOME</a>	<a href="#">MAIN UNIT MODULE OF THE IP CAMERA IPC-HUM8231-E1 - 1080p DAHUA</a>
		
	113.31 SEK 113.31 SEK	3121.92 SEK 3121.92 SEK
Sensor type	Passive Infra Red (PIR)	...
Standard	...	TCP/IP
Sensor	...	—
Detection angle	180 °	...
Matrix size	...	—
Range	12 m	...
Application	For outdoor use	...
Sensitivity adjustment	3 ... 2000 Lux (manual adjustment)	...
Recommended installation height	1.8 ... 2.5 m over the floor (wall-mounted)	...
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Adjusting the time of switching on the lighting	10 s ... 7 minutes	...
Maximal outputs load	1200 W (resistance load) 300 W (inductive load)	...
Pet immunity	—	...
"Index of Protection"	IP65	...
Color	White	...
Operation temp	-20 °C ... 40 °C	...
Operation modes	...	Main and sub streams may be in any configuration  Firmware 2.460.0000.14.R, build : 2017-07-20 • Main stream : 1920 x 1080, 1280 x 960, 1280 x 720 • Sub stream 1 : 704 x 576, 352 x 288 • Sub stream 2 : 1920 x 1080, 1280 x 720, 704 x 576, 352 x 288
Lens	...	—
View angle	...	—
Min. illumination	...	—
S/N ratio	...	> 50 dB
Audio	...	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
RS-485 interface	...	—



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RS-232 interface	...	✓
Bitrate	...	24 ... 9472 kbps - H.264 14 ... 5632 kbps - H.265
Main stream frame rate	...	25 fps @ 1920 x 1080
Network protocols	...	HTTP, HTTPS, IPv4/IPv6, TCP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPnP, NTP, QoS, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP
ONVIF	...	16.12
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Network interface	...	10/100 Base-T (RJ-45)
Alarm inputs / outputs	...	2 / 2
Mobile phones support	...	Port 37777 • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>
Default admin user / password	...	admin / -
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Power supply	220 V ... 240 V AC @ 50Hz	• 12 V DC / 580 mA, • PoE (802.3af)
Power consumption	...	< 7 W
Main features	...	• BLC - Back Light Compensation • HLC - High Light Compensation (spot) • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Configurable Privacy Zones • IVS analysis - crossing the line (tripwire), intrusion, abandoned/missing object, face detection
Length of the cable	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.16 kg	0.21 kg
Dimensions	120 x 80 x 52 mm	110 x 83 x 24 mm
Supported languages	...	English
Manufacturer / Brand	EL HOME	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00