




| | | | |
|----------------------------------|---|--|---|
| | IP CAMERA BCS-L-PIP12FW PINHOLE - 1080p 2.8 mm BCS Line | ADAPTER BNC-G/CINCH-W*P10 | OUTDOOR SIDE OPENING HOUSING PFH610N-JR-W-V2 DAHUA |
| |  |  |  |
| | 283.38 EUR 283.38 EUR | 2.30 EUR 2.30 EUR | 398.89 EUR 398.89 EUR |
| Standard | IP | ... | ... |
| External dimensions | ... | ... | 404 x 164 x 132 mm |
| In package | ... | 10 pcs The price for package | ... |
| Internal dimensions | ... | ... | 255 x 90 x 83 mm |
| Glass dimensions | ... | ... | Ø 60 mm |
| Resolution | 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p | ... | ... |
| Connector type | ... | Adapter BNC Socket / CINCH Plug | ... |
| Attachment of connector elements | ... | — | ... |
| Thermostat | ... | ... | ✓ |
| Sensor | 1/3 " Progressive Scan CMOS | ... | ... |
| Impedance | ... | 75 Ω | ... |
| Material | ... | Metal | Aluminum - powder painted + PC |
| IR illuminator | ... | ... | 100 m - RS-485 control |
| Lens | 2.8 mm @ F2.0 (pinhole) | ... | ... |
| View angle | 96 ° | ... | ... |
| Range of IR illumination | — | ... | ... |
| Main features | ... | <ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance | <ul style="list-style-type: none"> • The product is adapted to work outdoors (heater and fan cooler built-in) • Wiper - RS-485 control • Bracket not included in the kit |
| Memory card slot | — | ... | ... |
| Operation temp | ... | ... | -40 °C ... 60 °C |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... | ... |
| Alarm inputs / outputs | — | ... | ... |
| Audio | <ul style="list-style-type: none"> • Audio input • Microphone built-in, • Audio output • Bi-directional audio streaming support | ... | ... |
| Main stream frame rate | 25 fps @ 1080p | ... | ... |
| Interface | 10/100 Base-T (RJ-45) | ... | ... |
| WEB Server | Built-in | ... | ... |
| Max. number of on-line users | 20 | ... | ... |
| ONVIF | ✓ | ... | ... |
| Intelligent image analysis | <ul style="list-style-type: none"> • intrusion • crossing the line (tripwire) | ... | ... |

| | | | |
|-------------------------------|---|----------|---------------|
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Configurable Privacy Zones • Motion Detection • AWB - Auto White Balance • AGC - Automatic Gain Control • AES - Auto Electronic Shutter • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image • D-ZOOM - Digital Zoom : 16 x | ... | ... |
| Mobile phones support | <ul style="list-style-type: none"> Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager | ... | ... |
| Default IP address | 192.168.1.108 | ... | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... | ... |
| Web browser access ports | 80, 37777 | ... | ... |
| PC client access ports | 37777 | ... | ... |
| Mobile client access ports | 37777 | ... | ... |
| Port ONVIF | 80 | ... | ... |
| RTSP URL | <ul style="list-style-type: none"> rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream | ... | ... |
| Power supply | 12 V DC / 130 mA | ... | 24 V AC / 3 A |
| Power consumption | max. 1.56 W | ... | ... |
| Housing | Mini - Metal | ... | ... |
| Color | Black | ... | ... |
| "Index of Protection" | — | ... | IP66 |
| Mechanical protection class | — | ... | ... |
| Operation temp | -40 °C ... 60 °C | ... | ... |
| Weight | 0.08 kg | 0.007 kg | 2.79 kg |
| Dimensions | <ul style="list-style-type: none"> • 44 x 35 x 30 mm • 50 cm (cable length) | ... | ... |
| Supported languages | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian | ... | ... |
| Manufacturer / Brand | BCS Line | ... | DAHUA |
| Guarantee | 3 years | 2 years | 3 years |