

	CURRENT TRANSFORMER SC-16 ZAMEL	WIRELESS DOOR CHIME ATLO-DB-2/RX AC 230V ATLO	STRAIGHT SOCKET LE-50111 230 V 16 A LEGRAND	ELECTRIC CABLE YDY-3X2.5	INSULATION RESISTANCE METER + RCD TESTER UT-582+ UNLT	USB SOCKET TESTER UT-658-DUAL UNLT	METER OF CAPACITANCE, INDUCTANCE AND RESISTANCE UT-603	SPEAKER CABLE HI- FI2X0.5	
									
	171.61 SEK 171.61 SEK	79.02 SEK 79.02 SEK	84.38 SEK 84.38 SEK	14.50 SEK 14.50 SEK	1571.22 SEK 1571.22 SEK	195.33 SEK 195.33 SEK	615.76 SEK 615.76 SEK	3.57 SEK 3.57 SEK	
Support	MEW-01	ATLO-DB-2/TX	
Device type	Power meter via USB port	
Signaling mode	...	Optical - sound signaling	
Maximum continuous primary current	100 A	
Number of ring-tones	...	60	
Maximal current load	16 A	
Input socket type	1 x USB-A plug 1 x USB-C plug	
In section	100 m . Price for 1m when buying a whole roll	100 m . Price for 1m when buying a whole roll	
Grounding	✓	
Gear	3000 : 1	
AC voltage measurement	30 V ... 600 V ± (3% + 3) @ 1 V	...	---	...	
AC current measurement	---	...	
Electrical cable	max. 3 x 2.5 mm ²	---	...	
Frequency range	50/60 Hz	---	...	
Output socket type	1 x USB-A socket 1 x USB-C socket	
Volume adjustment	...	0 ... 90 dB - 5-step	
Cable terminals	automatic spring terminals	
LCD display	1.85 "	
Operation range	...	max. 150 m in open area	
Socket type	CEE 7/5	
Inner conductor	3 x 2.5 mm ² - Cu wire	2 x Ø 0.5 mm Cu-OFC Stranded wire	
Rated voltage	230 V / 50 Hz	750 V	
Frequency band	...	433 MHz	
"Index of Protection"	IP44	
Wire gauge	16 mm (max)	
IK rating	IK08	
DC voltage measurement	4 ... 24 V ± 1 %	---	...	
Color	Black	---	...	
Outer coating	Ø 9 mm PVC	---	PVC	
Coating color	White	---	Colorless	
DC current measurement	0.05 ... 3 A @ 0.01 A - USB-A 0.05 ... 5 A @ 0.01 A - USB-C	---	...	
Battery capacity measurement	0 ... 99999 mAh	---	...	
Energy measurement	0 ... 1000 Wh	---	...	
Equivalent resistance of the circuit measurement	1 ... 480 Ω	---	...	
Data storage	10 measurements	---	...	
Housing	Plastic	---	...	
Test of RCDs	• Working voltage: 220V ± 10 % • Test current: 10mA / 20mA / 30mA / 100mA / 300mA / 500mA • Switch-off time ranges : - x 1/2 - 10 / 20 / 30 / 100 / 300 / 500 mA @ 2000 ms - x 1 - 10 / 20 / 30 / 100 / 300 mA @ 1000 ms - x 5 - 500 mA @ 300 ms - AUTO RAMP - 10 / 20 / 30 / 100 / 300 / 500 mA @ 300 ms • AUTO RAMP test: measurement of shutdown current (with simultaneous measurement of time)	...	---	...	
Automatic change of measuring ranges	---	...	---	...	
USB	---	...	---	...	
Resistance measurement	200 Ω ± (0.8% + 3) @ 0.1 Ω 2 kΩ ± (0.8% + 1) @ 0.001 kΩ 20 kΩ ± (0.8% + 1) @ 0.01 kΩ 200 kΩ ± (0.8% + 1) @ 0.1 kΩ 2 MΩ ± (0.8% + 1) @ 0.001 MΩ 20 MΩ ± (2.0%(RD-12) + 5) @ 0.01 MΩ 2000 MΩ @ 1 MΩ - visual measurement	---	...
Operation temp	-15 °C ... 60 °C	0 °C ... 40 °C	...	---	...	
Permissible relative humidity	≤ 80 % (non-condensing)	...	---	...	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Capacitance measurement	2 nF ± (1% + 5) @ 0.001 nF 20 nF ± (1% + 5) @ 0.01 nF 200 nF ± (1% + 5) @ 0.1 nF 2 μF ± (4% + 5) @ 0.001 μF 20 μF ± (4% + 5) @ 0.01 μF 200 μF ± (4% + 5) @ 0.1 μF 600 μF @ 1 μF - visual measurement	...
Inductance measurement	2 mH ± (2% + 8) @ 0.001 mH, 20 mH ± (2% + 8) @ 0.01 mH, 200 mH ± (2% + 8) @ 0.1 mH, 2 H ± (5% + 5) @ 0.001 H, 20 H ± (5% + 5) @ 0.01 H, 200 H @ 0.1 H - visual measurement	...
Frequency measurement	45 Hz ... 65 Hz - frequencies displayed are for illustrative purposes	...	—	...
Square-wave signal duty ratio measurement	—	...
Temperature measurement	—	...
hFE	✓	...
Diode test	✓	...
Sound signal of the continuity test	✓	...
Checking TTL logic states	—	...
RS-232	—	...
Main features	Openable core	The number of cooperated doorbell buttons (transmitters) can be increased as required	• Phase switch 0° / 180° during RCD test, • Large, readable LCD display with backlight, • Buzzer, • Low battery level alarm, • Aesthetic and solid construction	...	• Large, readable LCD display with backlight • Hold - stopping the meter reading • Aesthetic and solid construction	...
Power supply	...	230 V AC	6 x 1.5V, type AA/LR6/FR6 battery - included	...	9V, type 6LR61 battery - included	...
Weight	0.09 kg	0.06 kg	0.068 kg	...	0.380 kg	0.065 kg	0.29 kg	...
Dimensions	45 x 34 x 31	95 x 68 x 65 mm	Ø 45 x 118 mm	...	160 x 100 x 69 mm	123 x 53 x 14 mm	172 x 84 x 41 mm	...
Manufacturer / Brand	ZAMEL	ATLO	LEGRAND	...	UNI-T	UNI-T	UNI-T	...
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00