



	ISOPROPYL ALCOHOL CLEANSER-IPA/400 SPRAY 400 ml	SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE
		
	6.38 EUR 6.38 EUR	112.16 EUR 112.16 EUR
Package	Spray 400 ml	...
Connectors	...	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs cable terminal • 1 pcs BNC
LAN ports	...	1 pcs RJ45 100 Mbps
LAN+PoE port configuration description	...	<ul style="list-style-type: none"> • xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+/-": 1, 2 pins; "+/-": 3, 6 pins) or ("+/-": 4, 5 pins; "+/-": 7, 8 pins) • xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W
Transmission range	...	<ul style="list-style-type: none"> < 1000 m @ Coaxial cable < 100 m @ xCOAX4-SW - Switch PoE < 100 m @ xCOAX4-CAM - IP Camera
LED indicators	...	<ul style="list-style-type: none"> • PoE • LAN • Link • 10Mb
Protections	...	<ul style="list-style-type: none"> • Overvoltage - LAN, BNC • Short-circuit - xCOAX4-SW
Main features	Spray formulation with a straw for easy application in hard-to-reach places	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Watchdog function - Coaxial cable

Power supply	...	xCOAX4-SW : <ul style="list-style-type: none"> • 10 ... 58 V DC - cable terminal • PoE 802.3af/at / PASSIVE • The output PoE voltage is equal to the input voltage
Power consumption	...	1.35 W (total)
Housing	...	Plastic (PC)
"Index of Protection"	...	IP20
Operation temp	...	-25 °C ... 65 °C
Weight	0.39 kg	0.033 kg (single element)
Dimensions	Ø 66 x 200 mm	<ul style="list-style-type: none"> • 73 x 52 x 20 mm - xCOAX4-SW • 73 x 52 x 20 mm - xCOAX4-CAM
Manufacturer / Brand	...	ATTE
Guarantee	...	3 years