






	<a href="#">ACCESS POINT 4G LTE Cat. 18, Wi-Fi 6, +ROUTER CUDY-LT18 2.4 GHz, 5 GHz, 574 Mbps + 1201 Mbps</a>	<a href="#">IP VANDALPROOF CAMERA IPC2325SB-DZK-10 - 5 Mpx 2.7 ... 13.5 mm - MOTOZOOM UNIVIEW</a>	<a href="#">IP CAMERA BCS-V-TIP45VSR5 - 5 Mpx 2.8 ... 12 mm - MOTOZOOM BCS View</a>	<a href="#">SWITCH POE APTI-POE0402-60W 4-PORT</a>	<a href="#">INDOOR SIREN SV-96WR24V</a>
					
	123428.57 HUF 123428.57 HUF	186497.14 HUF 186497.14 HUF	128571.43 HUF 128371.43 HUF	14476.19 HUF 14476.19 HUF	4355.24 HUF 4355.24 HUF
Standard	...	TCP/IP	TCP/IP	...	...
Current consumption	...	...	...	...	max. 170 mA
Sound pressure level	...	...	...	...	109 dB
Sensor	...	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	...	...
Matrix size	...	5 Mpx	5 Mpx	...	...
Management	...	...	...	...	...
LED diodes	...	...	...	LAN, WAN, PoE	...
Frequency range	• Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2100 MHz, 1800 MHz, 900 MHz, 800 MHz	...	...	...	...
Resolution	...	2880 x 1620 - 5 Mpx, 2560 x 1440 - 3.7 Mpx, 2304 x 1296 - 3 Mpx, 1920 x 1080 - 1080p	2560 x 1920 - 5 Mpx, 2560 x 1440 - 3.7 Mpx, 1920 x 1080 - 1080p 1280 x 720 - 720p	...	...
Transmission speed	...	...	...	• 10 / 100 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 4 x LAN & PoE ports	...
Antenna type	• 2 x Omnidirectional antenna Wi-Fi - Integrated • 2 x Omnidirectional antenna Wi-Fi - Internal antenna • 4 x Omnidirectional antenna 4G LTE / SMA connector for connecting an external antenna	...	...	...	...
Maximal output power	...	...	...	15.4 W / port PoE	...
Lens	...	2.7 ... 13.5 mm - Motozoom, AutoFocus	2.8 ... 12 mm - Motozoom	...	...
Maximal total power	...	...	...	60 W	...
MAC addresses table	...	...	...	2k	...
Standards	IEEE 802.11ax/n/b/g @ 2.4 GHz IEEE 802.11ax/ac/an/a @ 5 GHz	...	...	...	...
View angle	...	• 106 ° ... 30 ° (manufacturer data) • 104 ° ... 30 ° (our tests result)	97 ° ... 30 °	...	...
Certificates	...	...	...	CE	...
Compression	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
S/N ratio	...	> 56 dB	...	...	...
RS-485 interface	...	...	...	...	...
Range of IR illumination	...	50 m	50 m	...	...
Baud rates	• Wi-Fi 6 : 574 Mbps + 1201 Mbps, • LTE Cat. 18 : 1200 Mbps / 150 Mbps	...	...	...	...
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG	...	...	...
Alarm inputs / outputs	...	1 / 1	...	...	...
LAN ports	1 x 10/100/1000 Mbps - Uplink / LAN 3 x 10/100/1000 Mbps - LAN	...	...	6 x RJ45 ( 4 x IEEE 802.3af )	...
Audio	...	• External microphone input, • Audio output • Audio transmission via network • Bi-directional audio streaming support • Audio detection	...	...	...
LED indicators	Power, INTERNET, WiFi, LTE	...	...	...	...
SIM socket	2 x nano SIM	...	...	...	...
Main stream frame rate	...	25 fps @ 5 Mpx	• 20 fps - 5 Mpx • 25 fps - 3.7 Mpx	...	...
Network interface	...	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	...	...
DDNS	✓	...	...	...	...
DHCP server	✓	...	...	...	...
Protections	WPA2/WPA3 DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)	...	...
Network protocols	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, QoS, SSL / TLS, SSH	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv4, IPv6, Bonjour, UDP, SSL / TLS	...	...
WEB Server	...	Built-in	Built-in	...	...
Main features	...	<ul style="list-style-type: none"> <li>• Two SIM cards support</li> <li>• Internet access filtering</li> <li>• Static / dynamic routing</li> <li>• Built-in 4-port switch</li> <li>• Wireless transmission statistics</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• Firewall</li> <li>• QoS</li> <li>• Rate limit</li> <li>• Access control</li> <li>• Remote management</li> <li>• DMZ</li> <li>• parental control</li> <li>• Guest Network - a separate and secure network for guests</li> </ul>	...	<ul style="list-style-type: none"> <li>• 2 x Port Uplink</li> <li>• Range PoE : 200 m - The EXTEND mode enabled</li> </ul>	...
Max. number of on-line users	...	32	6	...	...
ONVIF	...	✓	✓	...	...
Operation temp	...	0 °C ... 45 °C	...	0 °C ... 55 °C	-5 °C ... 50 °C
Permissible relative humidity	...	5 % ... 95 % (non-condensing)	...	...	...
Mobile phones support	...	<ul style="list-style-type: none"> <li>• Access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	<ul style="list-style-type: none"> <li>• Port no.: 8000 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">BCS Manager</a></li> <li>• iOS (iPhone): Free application <a href="#">BCS Manager</a></li> </ul>	...	...
Default IP address	...	DHCP or 192.168.1.13	192.168.1.64	...	...
Default admin user / password	...	admin / 123456	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	...	80, 554	80	...	...
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	Port no.: 8000 or access by a cloud (P2P)	...	...
Mobile client access ports	...	80	8000	...	...
Port ONVIF	...	80	80	...	...
RTSP URL	...	<ul style="list-style-type: none"> <li>• rtsp://192.168.1.13:554/unicast/c1/s0/live</li> <li>- Main stream</li> <li>• rtsp://192.168.1.13:554/unicast/c1/s1/live</li> <li>- Sub stream</li> </ul>	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...	...
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, people counting, crowd gathering estimation, face detection</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - configurable Back Light Compensation</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>	...	...
Power supply	12 V DC / 2.5 A (power adapter included)	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 670 mA</li> </ul>	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 915 mA</li> </ul>	230 V AC	24 V DC
Power consumption	...	≤ 8 W	<ul style="list-style-type: none"> <li>• ≤ 12.9 W @ PoE (802.3at)</li> <li>• ≤ 11 W @ 12 V DC</li> </ul>	...	...
Housing	...	Compact, Metal	Compact, Metal	...	...
Color	...	White	White	...	Red

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	...	IP67	IP67	...	...
Vandal-proof	...	IK10	—	...	...
Operation temp	...	-30 °C ... 60 °C	-30 °C ... 60 °C	...	...
Weight	0.56 kg	0.93 kg	0.75 kg	0.65 kg	0.09 kg
Dimensions	253 x 161 x 48 mm	245 x 85 x 86 mm	Ø 105 x 244 mm	220 x 141 x 41 mm	122 x 73 x 45 mm
Supported languages	...	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English	...	...
Manufacturer / Brand	CUDY	UNIVIEW	BCS View	APTI	...
Guarantee	2 years	3 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00