





	<a href="#">REMOTE CONTROL FOR LED LIGHTING CONTROLLERS FUT092 2.4 GHz, MONO, CCT, RGB, RGBW, RGB CCT (RGBWW) MiBOXER / Mi-Light</a>	<a href="#">LED LIGHTING CONTROLLER WL5 Wi-Fi, 2.4 GHz, RGB CCT (RGBWW) 12 ... 48 V DC MiBOXER / Mi-Light</a>	<a href="#">RFID PROXIMITY CARD ATLO-104N13</a>	<a href="#">EXPANSION PLUG KS-12/8X120 KLIMAS</a>
				
	249.11 CZK 249.11 CZK	401.54 CZK 401.54 CZK	10.34 CZK 10.34 CZK	12.55 CZK 12.55 CZK
Standard	...	...	Unique EM 125kHz	...
Compatibility	...	...	EM4100/4102	...
Possibility of programming the serial number (ID)	...	...	—	...
Number of channels	4	...	...	...
Ability to write to internal memory	...	...	—	...
Material	...	...	...	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>
Rated voltage	...	12 ... 48 V DC	...	...
Serial Number overprint	...	...	✓	...
Drilling diameter	...	...	...	12 mm
Expansion plug length	...	...	...	80 mm
Screw dimensions	...	...	...	Ø 8 x 120 mm, SW-13
Power supply	2 x 1.5V, type AAA/LR03 battery (not included)	...	...	...
Maximal total load	...	<ul style="list-style-type: none"> <li>• 180 W @ 12 V,</li> <li>• 360 W @ 24 V</li> </ul>	...	...
Application	Works with LED lighting : (RGB/RGBW/RGB CCT/CCT/MONO) 12-24V LED strips	Works with LED lighting - (RGB/RGBW/RGB CCT/CCT/MONO) 12-24V LED strips	...	<ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> </ul>
Total maximal current	...	6 A / Channel, 15 A (total)	...	...
Number of inputs	...	1	...	...
Number of outputs	...	5 (power)	...	...
Connector type	...	<ul style="list-style-type: none"> <li>• screw terminals,</li> <li>• 5.5/2.1 socket / screw terminals - power input</li> </ul>	...	...
Wireless	2.4 GHz	<ul style="list-style-type: none"> <li>• Wi-Fi : IEEE 802.11 b/g/n,</li> <li>• 2.4 GHz</li> </ul>	...	...
Radio communication range (at open area)	30 m	30 m	...	...
Mobile phones support	...	<ul style="list-style-type: none"> <li>• Android: Free application <a href="#">MiBoxer</a>,</li> <li>• iOS (iPhone): Free application <a href="#">MiBoxer</a></li> </ul> Access by a cloud (P2P) - Gateway required WL-BOX2 <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	...	...

Main features	Touch control keys	<ul style="list-style-type: none"> <li>The repeater function allows you to transfer control to subsequent FUT035S / FUT036S / FUT038S / FUT039 modules even beyond the direct range of the remote control,</li> <li>Ability to work with any type of LED strip</li> </ul>	<ul style="list-style-type: none"> <li>Serial Number Format : 10H13D + WEG24A</li> <li>Range : ~ 11 cm</li> <li>The TK-4100 chip</li> </ul>	...
Housing	Plastic	Plastic	...	...
Color	White	White	...	...
Operation temp	-20 °C ... 60 °C	-10 °C ... 40 °C	...	...
Weight	0.07 kg (without battery)	0.06 kg	0.006 kg	...
Dimensions	137 x 55 x 21 mm	124 x 37 x 22 mm	86 x 54 x 1 mm	...
Manufacturer / Brand	MiBOXER / Mi-Light	MiBOXER / Mi-Light	ATLO	KLIMAS
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00