

	HANDS-FREE SWITCH AD- TL-6497/DIMM 5 V - 24 V DC ORNO	TURNBUCKLE VANT-5/PL	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC- EW2501-0140B - 5 Mpx 1.4 mm - Fish Eye DAHUA	SMART PROXIMITY SWITCH PROXISWITCH- V2/BLEBOX 12... 24 V DC	ACCESS CONTROLLER MC16-PAC-ST-3-KIT ROGER	STEEL LINE CROSS CLAMP ZLK-3
						
	3.92 GBP 3.92 GBP	1.19 GBP 1.19 GBP	201.11 GBP 201.11 GBP	11.47 GBP 11.47 GBP	556.93 GBP 556.93 GBP	0.27 GBP 0.27 GBP
Number of served transitions	3 (two-way)	...
Number of supported readers	12	...
Application	Works with LED lighting	Steel lines	...	Non-contact switching on and off	...	Steel lines max. Ø 3 mm
Rated voltage	5 V - 24 V DC	12 ... 24 V DC
Material	...	Metal	Metal
Standard	AHD, HD-CVI, HD-TVI, PAL
Number of users	unlimited (purchase of the appropriate license required)	...
Matrix size	5 Mpx
Sensor	1/2.8" CMOS
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Buffer memory	8 000 000 events buffer	...
Number of access zones	6	...
Maximal total load	• 5 V = 40 W • 12 V = 96 W • 24 V = 120 W	120 W
Number of alarm zones	6	...
Total maximal current	8 A	5 A
Battery backup support	12 V / 20 Ah	...
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx
Range of IR illumination	10 m
Detection range	10 mm ... 60 mm
IR illuminator power adjustment	Automatic
Detection method	Passive Infra Red (PIR)
Number of inputs	0	0
Communication	• Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface	...
Number of outputs	1	1
Lens	1.4 mm - Fish Eye, F2.0
Connector type	PCB (soldering)	screw terminals
View angle	180 °
Wireless	—	—
IR illuminator support	ICR - Movable InfraRed filter
Mobile phones support	—	—
S/N ratio	> 65 dB
Audio	Microphone built-in
Main features	<ul style="list-style-type: none"> • High power - max. 120 W • Possibility to adjust the light intensity depending on your needs • Small dimensions • Possible assembly in a profile • Simple and quick device installation 	<ul style="list-style-type: none"> • Screw diameter 5 mm • Work load 50 kg • Corrosion resistance 	...	<ul style="list-style-type: none"> • Operation modes : bistable, bistable + state memory, monostable NO, monostable NC, • Detection range : 3 cm • Trigger time : max. 8 s • Possibility to hide the sensor • Automatic calibration • LED indication 	<ul style="list-style-type: none"> • Metal housing • The MCX4D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	Corrosion resistance
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω

Main features	<ul style="list-style-type: none"> • 2D-DNR / 3D-DNR - Digital Noise Reduction • WDR - 120 dB - Wide Dynamic Range • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • Auto White Balance
Operation temp	-20 °C ... 50 °C	5 °C ... 40 °C	...
OSD menu	OSD menu available via recorder
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Power supply	12 V DC / 610 mA	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	...
Power consumption	≤ 7.3 W
Housing	—	...	Dome, Plastic	Plastic
"Index of Protection"	IP20	...	—	IP20
Vandal-proof	—
Color	—	...	White	Black
Operation temp	-30 °C ... 60 °C
Weight	0.001 kg	0.05 kg	0.26 kg	0.018 kg	4.08 kg	0.015 kg
Dimensions	48 x 10 x 6 mm	140 x 20 x 7 mm	Ø 126 x 44 mm	39 x 39 x 16 mm	405 x 365 x 120 mm	40 x 15 x 10 mm
Manufacturer / Brand	ORNO	...	DAHUA	BleBox	ROGER	...
Guarantee	2 years	2 years	5 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00