




	SMART ACTION TRIGGER INBOX/BLEBOX Wi-Fi, CR123A	SMART GATE AND DOOR CONTROLLER GATEBOX/BLEBOX Wi-Fi, 12 ... 24 V DC/AC	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH10-2WIRE-SET 2 PCS SET ATE	ANGULAR PLUG LE-50461 230 V 16 A LEGRAND
				
	22.68 EUR 22.68 EUR	45.16 EUR 45.16 EUR	89.51 EUR 89.51 EUR	10.90 EUR 10.90 EUR
Application	controlling devices, triggering actions	swing gates, sliding gates, garage gates, doors
Maximal current load	16 A
Rated voltage	3 V - Battery type CR123A	12 ... 24 V DC/AC	...	230 V / 50 Hz
Maximal total load	—	—	...	3500 W
Grounding	✓
Total maximal current	—	20 mA / Control output
Electrical cable	max. 3 x 1.5 mm ²
Number of inputs	4	2
Cable terminals	screw terminals
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG) 	...
Number of outputs	0	2
Plug type	CEE 7/7
Socket type	CEE 7/5
LAN ports	1 pcs RJ45 10 Mbps	...
Connector type	Connection cube, screw terminals	screw terminals
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Color	Black	Black	...	White / Gray
Connectors description	ETH10-2WIRE-TX : <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-: 1, 2 pins; "+/-": 3, 6 pins) or ("+/-": 4, 5 pins; "+/-": 7, 8 pins) • Power • DATA - 2-wire ETH10-2WIRE-RX : <ul style="list-style-type: none"> • PoE OUT - Passive PoE ("+"-: 4, 5 pins; "-": 7, 8 pins) • Power • DATA - 2-wire 	...
Transmission speed	10 Mbps	...

Transmission range	<ul style="list-style-type: none"> • 1000 m @ 2-wire • 100 m @ UTP : Switch PoE - ETH10-2WIRE-TX • 100 m @ UTP : ETH10-2WIRE-RX - IP Camera 	...
LED indicators	<ul style="list-style-type: none"> • Power • LAN • 2-wire 	...
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH10-2WIRE-TX 	...
Main features	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • µWiFi technology support, • Backup time : ~ 5 years 	<ul style="list-style-type: none"> • Control of the electric strike and automatic gate, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • µWiFi technology support 	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Operation modes - Set with jumpers 	Plug equipped with an additional socket outlet, compliant with the Uni-Schuko standard
Power supply	ETH10-2WIRE-TX : <ul style="list-style-type: none"> • 30 ... 56 V DC - PoE • 10 ... 56 V DC - Power ETH10-2WIRE-RX : <ul style="list-style-type: none"> • 10 ... 56 V - Power • The output PoE voltage is equal to the input voltage 	...
Power consumption	1.35 W (total)	...
Housing	Plastic	Plastic	Plastic (PC)	...
"Index of Protection"	IP20	IP20	IP20	...
Operation temp	-20 °C ... 50 °C	-20 °C ... 50 °C	-25 °C ... 65 °C	...
Weight	0.027 kg	0.03 kg	0.03 kg (single element)	0.07 kg
Dimensions	35 x 33 x 23 mm	50 x 34 x 18 mm	51 x 51 x 24 mm (single element)	79 x 75 x 55 mm
Manufacturer / Brand	BleBox	BleBox	ATTE	LEGRAND
Guarantee	2 years	2 years	3 years	2 years