




	LITHIUM BATTERY BAT-CR1225	ATTENUATOR TO-SC-GG/10DB 10 dB	NVR BCS-B-NVR1601(2.0) 16 CHANNELS BCS BASIC
			
	1.41 EUR 1.41 EUR	1.83 EUR 1.83 EUR	79.72 EUR 79.72 EUR
Rated voltage	3 V
Standard	TCP/IP
Type (size)	CR1225
Connector type	...	2 x Socket SC	...
Supported resolutions	max. 8 Mpx 4K UHD - 3840 x 2160 px
Attenuation	...	10 dB	...
Video outputs	1 pcs HDMI 4K 1 pcs VGA
Optical wavelength	...	1310 nm, 1550 nm	...
Audio support	16 Channels - Audio from cameras
Audio inputs	—
Housing	...	Plastic	...
Audio outputs	1 pcs Jack 3.5 mm socket
Image compression method	H.265+ / H.265 / H.264+ / H.264
Bitrate	max. 64 Mbps
Supported hard drives	1 x 6 TB SATA
Recording modes	Manual, Motion Detection, Schedule
External storage devices backup	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/9/16 channel synchronous playback
Network interface	1 x RJ-45 10/100/1000 Base-TX
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Network protocols	P2P, UPnP, DHCP
ONVIF	✓
Default admin user / password	admin / 123456
Default IP address	DHCP or 192.168.1.30
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	80
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
Alarm inputs / outputs	—
PTZ control	IP Speed Dome Cameras
Motion Detection	✓
USB	2 x USB 2.0
Mouse support	✓
IR remote controller in the set	—
Power supply	12 V DC / 2 A (power adapter included)
Power consumption	max. 3.2 W (without HDD)
Weight	0.002 kg	...	0.77 kg
Dimensions	Ø 12 x 2.5 mm	...	260 x 243 x 46 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	BCS BASIC
Guarantee	2 years	2 years	3 years

