



	SWITCH POE IP-5-11-E 5-PORT ATTE	RFID PROXIMITY CARD ATLO-307NR 13.56 MHz S50
		
	1441.81 NOK 1441.81 NOK	5.48 NOK 5.48 NOK
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE 	...
Standard	...	13.56 MHz S50
Compatibility	...	ISO/IEC 14443A
Management	—	...
Possibility of programming the serial number (ID)	...	—
Ability to write to internal memory	...	1 kB
Serial Number overprint	...	✓
LED diodes	Power, LAN	...
Transmission speed	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	...
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports 	...
Maximal total power	96 W	...
Operation modes	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 • Port LAN 6 - Uplink 	...

Main features	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The output PoE voltage is equal to the input voltage • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules 	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + 6H8D - Reverse number, • Range : ~ 10 cm, • The 6605 chip
Power supply	230 V AC - cable terminals	...
Weight	1.4 kg	0.006 kg
Dimensions	255 x 205 x 95 mm	86 x 54 x 0.8 mm
Manufacturer / Brand	ATTE	ATLO
Guarantee	3 years	2 years