



	IP SPEED DOME CAMERA OUTDOOR OMEGA-40P18-6-AI - 5 Mpx 5.35 ... 96.3 mm	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps
		
	256.36 EUR 256.36 EUR	107.61 EUR 107.61 EUR
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	5 Mpx	...
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Frequency range	...	<ul style="list-style-type: none"> • Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz
Lens	5.35 ... 96.3 mm	...
Antenna type	...	<ul style="list-style-type: none"> • 4 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Integrated
View angle	<ul style="list-style-type: none"> • 59 ° ... 3.6 ° (manufacturer data) • 50 ° ... 3.8 ° (our tests result) 	...
Standards	...	IEEE 802.11 b/g/n/ac
Optical zoom	x 18	...
Auto IR illuminator	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions	...
Range of IR illumination	80 m	...
Video output	—	...
Baud rates	...	<ul style="list-style-type: none"> • Wi-Fi : 866 Mbps + 300 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps
Rotation speed (manual control)	1 °/s ... 120 °/s (horizontal) , 1 °/s ... 30 °/s (vertical)	...
Horizontal rotation range	360 ° continuous	...

Vertical rotation range	0 ° ... 93 °	...
RS-485 interface	—	...
LAN ports	...	1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN
Number of presets	255	...
Horizontal scan	✓	...
Image compression method	H.265 / H.264	...
LED indicators	...	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN
SIM socket	...	1 x mini SIM
Audio	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Bi-directional audio streaming support • Voice prompts in English or Chinese 	...
Alarm inputs / outputs	—	...
DDNS	...	✓
Memory card slot	✓	...
DHCP server	...	✓
Firmware update	...	✓
Network interface	10/100 Base-T (RJ-45)	...
Protections	Overvoltage	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Management interface	...	Web browser
Transmitter power	...	< 20 dBm
Main features	...	<ul style="list-style-type: none"> • Built-in 5-port switch • RESET button • Remote management
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP	...
Main stream frame rate	20 fps @ 5 Mpx 25 fps @ 4 Mpx	...
WEB Server	Built-in	...
ONVIF	✓	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Default IP address	192.168.1.168	...

Default admin user / password	admin / admin The administrator password should be set at the first start	...
Web browser access ports	80	...
Port ONVIF	8999	...
RTSP URL	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream	...
Route settings	8	...
OSD menu	preset 95	...
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion • Local recording : Motion Detection, Schedule, continuous • WDR - Wide Dynamic Range • ROI - improve the quality of selected parts of image • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • Auto White Balance • AGC - Automatic Gain Control • IR illuminator optimization • Mirror - Mirror image • Motion Detection - Split the screen into zones 16 x 12 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at) • 12 V DC / 3 A (power adapter included) 	12 V DC / 1 A (power adapter included)
Housing	Speed Dome, Metal	...
Color	White + Black	...
"Index of Protection"	IP66	...
Operation temp	-40 °C ... 60 °C	...
Weight	1.51 kg (with bracket)	0.42 kg
Dimensions	200 x 269 x 137 mm (with bracket)	238 x 149 x 33 mm

Supported languages	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	OMEGA	...
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00