



	SWITCH POE DS-3E0526P-E 24-PORT SFP Hikvision	SPEAKER CABLE HL- FL2X0.5	UPS AT-UPS1500S-RT-RACK 1500 VA EAST	DC FILTER FDC-08 TO SWITCHING ADAPTERS	EXPANSION PLUG KS-10/6X120 KLIMAS	IP CAMERA IPC-HDW1439V-A-IL-BLACK Smart Dual Light - 3.7 Mpx 2.8 mm DAHUA
						
	441.99 EUR 441.99 EUR	0.32 EUR 0.32 EUR	310.43 EUR 310.43 EUR	9.70 EUR 9.70 EUR	0.30 EUR 0.30 EUR	160.10 EUR 160.10 EUR
Standard	...	...	...	...	...	IP
Power adapter type	...	...	Line-interactive	...	...	...
Maximal current	...	...	...	0.8 A	...	...
Nominal power	...	...	1200 W	...	...	...
Apparent Power	...	...	1500 VA	...	...	...
Power connectors type	...	...	...	2.1/5/5 mm plug	...	...
In section	...	<b>100 m . Price for 1m when buying a whole roll</b>	...	...	...	...
Material	...	...	...	...	• Expansion plug, Polypropylene • Screw, Steel galvanized	...
Input voltage	...	...	230 V AC ± 25 %	...	...	...
Drilling diameter	...	...	...	...	10 mm	...
Expansion plug length	...	...	...	...	60 mm	...
Input frequency	...	...	50 / 60 Hz (auto detection)	...	...	...
Inner conductor	...	2 x Ø 0.5 mm Cu-OFC Stranded wire	...	...	...	...
Screw dimensions	...	...	...	...	Ø 6 x 120 mm, SW-10	...
Output voltage	...	...	230 V AC ± 10 % (Pure Sine Wave)	...	...	...
Outer coating	...	PVC	...	...	...	...
Coating color	...	Colorless	...	...	...	...
Application	...	...	...	...	• Concrete • Solid clay brick • Solid sand-lime brick	...
Output frequency	...	...	50 / 60 Hz ± 1 %	...	...	...
Voltage adjustment	...	...	—	...	...	...
LAN ports	• 24 x RJ45 10/100/1000 Base-TX ( 24 x PoE (802.3af/at) ), • 1 x RJ45 10/100/1000 Base-TX - Uplink, • 1 x port SFP 10/100/1000 Base-TX - Uplink	...	...	...	...	...
Frequency adjustment	...	...	—	...	...	...
Resolution	...	...	...	...	...	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Transfer time	...	...	≤ 10 ms	...	...	...
Charging time (recover to 90% capacity)	...	...	8 hours	...	...	...
Sensor	...	...	...	...	...	1/2.9 " Progressive Scan CMOS
Lens	...	...	...	...	...	2.8 mm
Battery	...	...	2 x 12V/9Ah	...	...	...
Transmission speed	• 10 / 100 / 1000 Mbps - 24 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports	...	...	...	...	...
View angle	...	...	...	...	...	94 °
White light LED illuminator range	...	...	...	...	...	30 m
Maximal output power	30 W / port PoE	...	...	...	...	...
Range of IR illumination	...	...	...	...	...	30 m
Maximal total power	370 W	...	...	...	...	...
MAC addresses table	8k	...	...	...	...	...
Management	—	...	...	...	...	...
Image compression method	...	...	...	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate	...	...	...	...	...	25 fps @ 3.7 Mpx
Memory card slot	...	...	...	...	...	—
Alarm inputs / outputs	...	...	...	...	...	—
LED diodes	Power, Link/Act, PoE, PoE Max	...	...	...	...	...
Audio	...	...	...	...	...	• Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Audio detection
Interface	...	...	...	...	...	10/100 Base-T (RJ-45)
Certificates	CE, FCC, RoHS	...	...	...	...	...
WEB Server	...	...	...	...	...	Built-in
Max. number of on-line users	...	...	...	...	...	6
ONVIF	...	...	...	...	...	✓
Operation temp	-10 °C ... 55 °C	...	...	...	...	...
Mobile phones support	...	...	...	...	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>
Default IP address	...	...	...	...	...	192.168.1.108
Default admin user / password	...	...	...	...	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	...	...	...	...	80, 37777

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

SAP Code	301801380	...	...	...	...	...
Estimated battery operation time	...	...	<ul style="list-style-type: none"> <li>• 41 minutes @ 100 W,</li> <li>• 22 minutes @ 200 W,</li> <li>• 15 minutes @ 300 W,</li> <li>• 9 minutes @ 400 W,</li> <li>• 6.5 minutes @ 500 W,</li> <li>• 4 minutes @ 600 W,</li> <li>• 2 minutes @ 700 W,</li> <li>• 2 minutes @ 800 W,</li> <li>• 1.5 minutes @ 900 W,</li> <li>• 42 s @ 1000 W</li> </ul>	...	...	...
PC client access ports	...	...	...	...	...	37777
Mobile client access ports	...	...	...	...	...	37777
Port ONVIF	...	...	...	...	...	80
Number of outputs	...	...	6 pcs - 3 x CEE 7/3 (Schuko), 3 x IEC C13	...	...	...
Management software	...	...	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)	...	...	...
RTSP URL	...	...	...	...	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Protections	...	...	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overvoltage - RJ45</li> <li>• Ethernet filter</li> <li>• Output voltage filtering</li> <li>• DC filter to eliminate interferences - EMI/RFI</li> </ul>	...	...	...
Main features	...	...	...	...	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BL/HLIC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Motion Detection - max. 4 configurable zones</li> <li>• Privacy zones - max. 4</li> <li>• Intelligent image analysis : Human detection</li> </ul>
Housing	Metal	...	...	...	...	Dome - Metal + Plastic
Operation state indication	...	...	<ul style="list-style-type: none"> <li>• LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, LED diodes,</li> <li>• Sound signaling</li> </ul>	...	...	...
Color	...	...	...	...	...	Black
"Index of Protection"	...	...	...	...	...	IP67
Mechanical protection class	...	...	...	...	...	-
Power supply	100 ... 240 V AC	...	...	...	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 380 mA</li> </ul>
Power consumption	...	...	...	...	...	<ul style="list-style-type: none"> <li>• ≤ 5.7 W @ PoE</li> <li>• ≤ 4.6 W @ 12 V DC</li> </ul>
Operation temp	...	...	...	...	...	40 °C ... 60 °C
Main features	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Overvoltage protection : 6 kV - PoE ports</li> <li>• Can be mounted in a Rack 19" cabinet</li> </ul>	...	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Excellent microprocessor control guarantees high reliability</li> <li>• COLD START function for manual switch to the battery power supply</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Battery charge and maintenance control</li> <li>• 2 x RJ45 - Input / Output</li> <li>• Port USB 2.0 - Access from PC</li> <li>• Remote management - UPSmart application (included)</li> <li>• Optical - sound signaling</li> <li>• Built-in EMI, RFI filter</li> <li>• Network card slot</li> <li>• Can be mounted in a Rack 19" cabinet</li> <li>• The device works with power supply adapters having Active Power Factor Correction (APFC)</li> </ul>	...	...	...
Supported languages	...	...	...	...	...	English, Spanish, Russian
Application	...	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network servers, workstations</li> <li>• Industrial Equipment</li> </ul>	...	...	...
Housing type	...	...	Rack/Tower 2-in-1 Design	2,1/5.5 mm socket	...	...
Operation temp. / Relative humidity	...	...	5 °C ... 40 °C / ± 93 % (non-condensing)	...	...	...
Weight	2.9 kg	...	17.1 kg	0.02 kg	...	0.33 kg
Dimensions	440 x 221 x 44 mm	...	440 x 132 x 410 mm ; RACK 19" , 3U	26 x 21 x 16 mm	...	Ø 110 x 101 mm
Manufacturer / Brand	Hikvision	...	EAST	DELTA	KLIMAS	DAHUA
Guarantee	3 years	2 years	2 years	3 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00