

	DOOR CONTROLLER ACCO-KP2 SATEL	POWER DISTRIBUTION UNIT PR-1.5M-6G-SW/W (6 OUTLETS) 1.3 m
		
	453.00 PLN 453.00 PLN	22.82 PLN 22.82 PLN
Input lines	12	...
Output lines	12	...
Rated voltage	...	220 ... 240 V AC / 50 Hz
Total maximal current	...	10 A
Operation modes	<ul style="list-style-type: none"> • Autonomous operation, • Work in the ACCO/ACCO NET system 	...
Maximal total load	...	2500 W
Number of outlets	...	6 grounded outlets 10A/250V CEE 7/5
Fuse	...	—
Switch	...	✓
Wire gauge	...	3 x 1.5 mm ²
Outputs rating	<ul style="list-style-type: none"> • 50 mA / 12 V DC - (OUT 1-12) • 0.5 A / 12 V DC - (+G 1-4) 	...
Length of the cable	...	1.3 m
Housing	...	Plastic
Relay switching voltage	250 V AC, 30 V DC	...
Color	...	White
Relay contacts load	8 A	...
Communication	RS-485	...

Main features	<ul style="list-style-type: none"> • 5 programmable input lines NO/NC • Additional dedicated inputs for connecting readers, monitoring the presence of readers, and connecting the tamper circuit • power input • 2 programmable low-current output lines OC • Additional outputs dedicated to connecting readers • Relay output to control the electromagnetic lock, gate controllers or other devices that activate the door • 4 power outputs 12 V/0.5 A • Support for single door with entry and exit authorization, • 1024 users • Possibility to add different privileges to the users • Identification: Card and/or PIN, Dallas iButton • History of 24 576 events • Recording of information about Time&Attendance • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Holiday access schedules • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Scheduled door locking and unlocking • Limiting of accesses • Compliance with the EM-MARIN, Wiegand 26-56bit, DALLAS protocol • micro USB socket - The ability to firmware upgrade • Its own clock with battery backup • LED indicators displaying the device's operating status • APS power socket - SATEL power adapter (not included) 	...
Power supply	12 V DC	...



Current consumption	• 110 mA (Standby mode) • 480 mA (operation)	...
Permissible relative humidity	93 % ± 3 %	...
Weight	0.11 kg	0.4 kg
Dimensions	142 x 71 x 17 mm	313 x 54 x 46 mm
Manufacturer / Brand	SATEL	...
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00