



	<a href="#">ALARM KIT ATLO-AZ-WG13A-TUYA</a>	<a href="#">POWER CORD CABLE CEE-77/IEC-C5 1.5 m</a>
		
	16576.19 HUF 16576.19 HUF	1097.14 HUF 1097.14 HUF
Aspect ratios	2.4 " TFT LCD	...
Number of supported wireless devices	max. 30 pcs	...
Cable	...	Socket C5 (cloverleaf) / Power connector
Length of the cable	...	1.5 m
Voltage	...	max. 250 V
Number of supported remote control keyfobs	max. 8 pcs, In the kit : 2 pcs	...
Current	...	max. 2.5 A
The RFID cards/keyfobs support	Unique EM 125kHz	...
Number of supported wireless sirens	1 pcs	...
PIR detectors included	1 pcs, Wireless	...
Magnetic contact included	1 pcs, Wireless	...
Keyboard included	✓	...
Expander included	—	...
Wireless	433 MHz	...
Zones	99 (wireless zones)	...
Timers	✓	...
Users + admins	6	...
Default administrator password	6666	...
Default user password	1234	...
Built-in modules	GSM, WiFi	...
Access from PC	—	...
Mobile phones support	Access by a cloud (P2P) • The <a href="#">Tuya Smart</a> free application on Android • The <a href="#">Tuya Smart</a> free application on iOS Remote control of the control panel via SMS, Tuya Smart application	...
Supported languages	Chinese, English, German, Russian, Spanish, Polish, Italian, French, Portuguese, Greek, Romanian	...

Power supply	<ul style="list-style-type: none"> <li>• 5 V DC / 2 A (power adapter included)</li> <li>• Built-in battery that maintains the control panel operation during a power failure : 3.7 V / 1000 mAh</li> </ul>	...
Housing	Plastic	...
Operation temp	-10 °C ... 55 °C	...
Detection	Opening the door or window	...
Alarm signaling	Signal to control panel	...
Alarm inputs	—	...
Battery power supply	2 x 1.5V, type AAA/LR03 battery (included)	...
Frequency range	433 MHz 433 MHz	...
Radio communication range (at open area)	max. 30 m	...
Detection angle / Detection range	120 ° / 12 m (max)	...
Main features	Code 1527 data encryption	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Solid workmanship</li> </ul>
Frequency band	433 MHz	...
Main features	<ul style="list-style-type: none"> <li>• Bidirectional communication,</li> <li>• SMS notification about alarm and power failure,</li> <li>• LED indication,</li> <li>• LCD display,</li> <li>• Built-in alarm siren - 100 dB,</li> <li>• Alarm mute function</li> <li>• LED indication</li> <li>• One-touch action buttons : arm, disarm, arming only perimeter protection zones, SOS</li> </ul>	...
Battery	1 x CR2032 3V (included) 1 x CR2025 (included)	...
Connector	Jack 3.5 mm	...
Sound pressure level	120 dB	...
Color	Black White	...
Weight	0.2 kg • 0.02 kg - Transmitter • 0.01 kg - Magnet 0.06 kg 0.02 kg 0.06 kg	0.17 kg

Dimensions	185 x 125 x 14 mm • 60 x 23 x 13 mm - Transmitter • 40 x 13 x 10 mm - Magnet 105 x 40 x 27 mm 58 x 32 x 11 mm 63.5 x 54 x 47.5 mm	...
Manufacturer / Brand	ATLO	...
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00