



	EXPANSION PLUG KW-8/4X40 KLIMAS	IP VANDALPROOF CAMERA DS-2CD2763G2-IZS(2.8-12MM) ACUSENSE - 6 Mpx - MOTOZOOM Hikvision
		
	0.10 CAD 0.10 CAD	703.26 CAD 703.26 CAD
Standard	...	TCP/IP
Sensor	...	1/2.4 " Progressive Scan CMOS
Matrix size	...	6 Mpx
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized 	...
Drilling diameter	8 mm	...
Expansion plug length	40 mm	...
Screw dimensions	Ø 4 x 40 mm, PZ-2	...
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick 	...
Resolution	...	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 ... 12 mm - Motozoom
View angle	...	<ul style="list-style-type: none"> • 106 ° ... 35 ° (manufacturer data) • 108 ° ... 35 ° (our tests result)
Range of IR illumination	...	40 m
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 512GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
Audio	...	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, WebSocket, WebSockets, SRTP, SFTP
WEB Server	...	Built-in, Web Viewer
Max. number of on-line users	...	6
ONVIF	...	19.12
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS (iPhone): Free application Hik-Connect

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Main stream frame rate	...	25 fps @ 6 Mpx
Main features	...	<ul style="list-style-type: none"> • Camera from AcuSense series • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Mirror - Mirror image • Day/night mode • Auto White Balance • AGC - Automatic Gain Control • Privacy zones - max. 4 • Smart motion detection (with recognizing people and vehicles) • Sharpness - sharper image outlines • Intelligent image analysis : Filtering of false alarms based on the recognition of persons and vehicles : intrusion, crossing the line (tripwire), face detection
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 880 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 12.5 W @ PoE (802.3af) • ≤ 10.5 W @ 12 V DC
Housing	...	Dome - Metal
Color	...	White
"Index of Protection"	...	IP67

Vandal-proof	...	IK10
Operation temp	...	-30 °C ... 60 °C
Weight	...	0.98 kg
Dimensions	...	Ø 153 x 112 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	KLIMAS	Hikvision
SAP Code	...	311316145
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00