



	AHD, HD-CVI, HD-TVI CAMERA APTI-H50PV21-28W 2Mpx / 5Mpx 2.8 mm	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-B-MK82800 - 8.3 Mpx 4K UHD 2.8 mm BCS BASIC
		
	23.26 EUR 23.26 EUR	57.91 EUR 57.91 EUR
Standard	AHD, HD-CVI, HD-TVI	AHD / HD-CVI / HD-TVI / CVBS
Sensor	1/3 " Progressive Scan CMOS	1/2.3 " Progressive Scan CMOS
Matrix size	5 Mpx	8.3 Mpx
Resolution	<ul style="list-style-type: none"> • 2592 x 1944 - 5 Mpx @ AHD, HD-TVI, • 2560 x 1440 - 3.7 Mpx @ AHD, HD-TVI, HD-CVI, • 1920 x 1080 - 1080p @ AHD, HD-CVI, HD-TVI 	3840 x 2160 - 8.3 Mpx 4K UHD @ 15 fps
Range of IR illumination	20 m	30 m
IR illuminator power adjustment	Automatic	Automatic
Lens	2.8 mm	2.8 mm, F1.2
View angle	<ul style="list-style-type: none"> • 89 ° (manufacturer data) • 83 ° (our tests result) 	<ul style="list-style-type: none"> • 104 ° (manufacturer data) • 106 ° @ AHD / HD-CVI / HD-TVI (our tests result)
Video output	1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI - selectable by switch	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω, selectable by switch
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Sharpness - sharper image outlines • Auto White Balance 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • FLC - The technology eliminates the tiring eyes flickering image effect • Day/night mode • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Auto White Balance • Mirror - Mirror image
Power supply	12 V DC / 180 mA	12 V DC / 420 mA
Power consumption	≤ 2.2 W	< 5 W

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

OSD menu	OSD menu available via recorder	OSD menu available via recorder
Housing	Dome - Plastic	Dome, Metal
Color	White	Graphite
"Index of Protection"	—	IP65
Vandal-proof	—	—
Operation temp	-20 °C ... 60 °C	-20 °C ... 60 °C
Weight	0.11 kg	0.27 kg
Dimensions	Ø 84 x 69 mm	Ø 94 x 80 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...
Manufacturer / Brand	APTI	BCS BASIC
Guarantee	2 years	3 years