



	<a href="#">ACCESS POINT 4G LTE +ROUTER TL-MR6400 300Mb/s TP-LINK</a>	<a href="#">NVR NVR616RH-32-XI 32 CHANNELS WizMind DAHUA</a>
		
	869.07 NOK 869.07 NOK	75859.91 NOK 75859.91 NOK
Frequency range	2.4 GHz	...
Standard	...	IP
Supported resolutions	...	max. 32 Mpx
Video outputs	...	<ul style="list-style-type: none"> <li>• 2 pcs HDMI 4K</li> <li>• 1 pcs HDMI 8K</li> <li>• 1 pcs HDMI</li> <li>• 2 pcs VGA</li> </ul>
Antenna type	2 x WiFi built-in , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna	...
Standards	802.11n/g/b IEEE 802.3/3u	...
Audio support	...	<ul style="list-style-type: none"> <li>• 32 Channels - Audio from cameras,</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>
Audio inputs	...	1 pcs CINCH
Audio outputs	...	2 pcs CINCH
Image compression method	...	Smart H.265+ / H.265 / Smart H.264+ / H.264
Bitrate	...	max. 1280 Mbps
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps	...
Supported hard drives	...	16 x 20 TB SATA + 1 x eSATA , Raid 0/1/5/6/10
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Modulation type	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM	...
Searching and playback the records	...	<ul style="list-style-type: none"> <li>• Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>• Advanced searching (to the one second accuracy)</li> <li>• Smart Playback function</li> <li>• Records playback from max. 16 channels in the same time</li> </ul>
Network interface	...	4 x RJ-45 10/100/1000/2500 Base-TX
LAN ports	<ul style="list-style-type: none"> <li>• 1 x 10/100 Mbps - LAN/WAN</li> <li>• 3 x 10/100 Mbps - LAN</li> </ul>	...
Network functions	...	Full support via network, Remote records copying, Web-Server built-in

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Receiver sensitivity	<ul style="list-style-type: none"> <li>• 11g 54M: -74dBm</li> <li>• 11n HT20: -71dBm</li> <li>• 11n HT40: -67dBm</li> </ul>	...
LTE	✓	...
ONVIF	...	22.06
QSS	✓	...
Default IP address	...	192.168.1.108
WDS	✓	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
Permissible relative humidity	max. 95 % (non-condensing)	...
Mobile phones support	...	<p>Port no.: 37777 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul> <p>See how to configure the P2P function in Dahua recorders and how to enable the mobile application</p>
Main features	<ul style="list-style-type: none"> <li>• SIM socket</li> <li>• WPS/RESET button</li> </ul>	...
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
RTSP URL	...	<ul style="list-style-type: none"> <li>• rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&amp;subtype=0 - Main stream</li> <li>• rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&amp;subtype=1 - Sub stream</li> </ul>
USB	...	<ul style="list-style-type: none"> <li>• 2 pcs USB 2.0</li> <li>• 2 pcs USB 3.0</li> </ul>
Serial ports	...	<ul style="list-style-type: none"> <li>• 2 pcs RS-485</li> <li>• 1 pcs RS-232</li> </ul>
Alarm inputs / outputs	...	32 / 16
PTZ control	...	<ul style="list-style-type: none"> <li>• IP Speed Dome Cameras</li> <li>• RS-485 - PELCO-D/P and others</li> </ul>
Intelligent image analysis	...	✓
Motion Detection	...	✓



Main features	...	<ul style="list-style-type: none"> <li>• Intelligent image analysis : IVS analysis - 10 rules, scene changing, face detection,</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Face recognition - supports 6 types of facial attributes extraction</li> <li>• Face recognition and analysis in real time (up to 16 photos per second)</li> <li>• Support for up to 40 face databases, including 300 000 face images</li> <li>• metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles)</li> <li>• AcuPick support - technology that uses artificial intelligence on both front-end and back-end to search through massive amounts of video data to quickly locate targets with high precision</li> <li>• EPTZ - advanced target detection and tracking algorithms that trigger alarms - can simultaneously zoom and track many people and/or vehicles</li> </ul> <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> <li>• ANPR</li> <li>• Authorized and unauthorized license plate lists: up to 20 000 records</li> <li>• counting people / vehicles</li> <li>• crowd gathering estimation</li> <li>• heat map</li> </ul>
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	—
Power supply	9 V DC / 1 A (power adapter included)	<ul style="list-style-type: none"> <li>• 100 ... 240 V AC @ 50 ± 2 Hz</li> <li>• Redundant power supply</li> </ul>
Power consumption	...	max. 25 W (without HDD)
Operation temp	0 °C ... 40 °C	-10 °C ... 55 °C
Weight	0.354 kg	13.03 kg
Dimensions	202 x 141 x 34 mm	485 x 529 x 133 mm
Supported languages	...	Polish, English
Manufacturer / Brand	TP-LINK	DAHUA
Guarantee	3 years	3 years