




	POWER DISTRIBUTION UNIT ACAR-504/WF/RACK	ACCESS CONTROLLER ASI1212F DAHUA
		
	58.94 AUD 58.94 AUD	368.58 AUD 368.58 AUD
Rated voltage	230 V AC	...
Cards support	...	13.56 MHz S50
Rated current	10 A (total)	...
Reading distance of prox-keys	...	1 ... 3 cm
Response time	< 25 ns	...
Keyboard built-in	...	—
Autonomous operation	...	✓
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Battery backup support	...	—
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Input lines	...	3
Output lines	...	3
Nominal stroke current	2.5 kA (L/N) - 8/20 μs	...
Identification time	...	< 1.5 s
Maximum stroke current	6.5 kA (L/N) - 8/20 μs	...
Leak current	< 0.5 mA	...
Number of outlets	5 grounded outlets 10A/250V	...
Communication	...	<ul style="list-style-type: none"> • RS-485 • Wiegand • LAN
Switch	two-way, with light indication	...
RS-485 interface	...	✓
Length of the cable	2.7 m	...
RS-232 interface	...	—
Wiegand interface	...	✓
Housing	RACK 19", 1U, Plastic - non-flammable	...
Network interface	...	10/100 Base-T
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start

USB	...	—
Memory card slot	...	—
Internal memory	...	Support storage of 150 000 records
Power supply	...	12 V DC / 1 A
Main features	...	<ul style="list-style-type: none"> • Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen • Fingerprint reader built-in • Memory of 3000 fingerprint patterns • Possible connection of the external ASR series reader (read in/out door control) • Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above • Remote access verification • Tamper detection - removing from mounting surface • Support for door contact and exit button • Indication of forced entry and the lack of closing doors • 30000 indexed users • Possibility to configure access groups • 128 General Purpose Schedules • 128 time periods within single Schedule • Holiday Schedules • Anti-passback • Integration with an alarm system via in/out line • Remote programming from PC
"Index of Protection"	...	—
Operation temp	...	-10 °C ... 45 °C
Permissible relative humidity	...	5 ... 90 % (non-condensing)
Dimensions	383 x 58 x 55 mm	115 x 115 x 32 mm
Weight	0.59 kg	0.22 kg
Supported languages	...	English
Manufacturer / Brand	...	DAHUA

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	2 years	3 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00