






	RFID PROXIMITY CARD ATL0-307S*P200 13.56 MHz S50	REAR SUPPORT FOR THE MOUNTING PROFILE USP- TN-600 FOR SOLAR PANELS	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI- AI71FRTD 4.5 mm - 1080p	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH10-2WIRE-SET 2 PCS SET ATTE	POE SWITCH / EXTENDER PFT1320 3-PORT
					
	51.92 USD 51.92 USD	7.01 USD 7.01 USD	62.30 USD 62.30 USD	95.78 USD 95.78 USD	19.52 USD 19.52 USD
Material	...	Aluminum
Scanning system	Progressive
In package	200 pcs The price for package
Standard	13.56 MHz S50
Compatibility	ISO/IEC 14443A
Possibility of programming the serial number (ID)	—
Optical zoom	—
Ability to write to internal memory	1 kB
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG) 	...
Serial Number overprint	—
LAN ports	1 pcs RJ45 10 Mbps	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af)
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS 1/5 " GC2145
Matrix size	2.1 Mpx 2 Mpx
Management	—
Pixel pitch	1.75 μm
Lens	4.5 mm 2.4 mm
LED diodes	Link, Act
View angle	68 ° 70 °
Resolution	1920 x 1080 - 1080p 800 x 600 - 0.48 Mpx
Maximal output power	15.4 W @ port PoE - First device
Standard	TCP/IP
Range of IR illumination	5 m
White light LED illuminator range	5 m
Temperature measurement	✓
Temperature measurement range	35 °C ... 42 °C
Accuracy of temperature measurement	± 0.3 °C
Range	100 m - Input 100 m - Output

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Face recognition distance	0.5 m ... 2.3 m (max 30 000 faces in the database)
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %
Temperature measurement distance	0.5 m ... 1.3 m optimal distance : 0.75 m
Connectors description	<ul style="list-style-type: none"> ETH10-2WIRE-TX : • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+" : 1, 2 pins; "+-" : 3, 6 pins) or ("+" : 4, 5 pins; "+-": 7, 8 pins) • Power • DATA - 2-wire ETH10-2WIRE-RX : • PoE OUT - Passive PoE ("+" : 4, 5 pins; "-" : 7, 8 pins) • Power • DATA - 2-wire 	...
Internal memory	Support storage of 25 000 records
Video output	—
Transmission speed	10 Mbps	10 / 100 Mbps
RS-485 interface	✓
Wiegand interface	✓
Memory card slot	—
Alarm inputs / outputs	0 / 2 (bolt control, signaling of exceeding the temperature)
Relay output	NO, NC
Audio	Speaker built-in
Transmission range	<ul style="list-style-type: none"> • 1000 m @ 2-wire • 100 m @ UTP : Switch PoE - ETH10-2WIRE-TX • 100 m @ UTP : ETH10-2WIRE-RX - IP Camera 	...
Network interface	10/100 Base-T (RJ-45)
LED indicators	<ul style="list-style-type: none"> • Power • LAN • 2-wire 	...
Network protocols	IPv4, HTTP, HTTPS, TCP/IP
WEB Server	Built-in
Max. number of on-line users	20
ONVIF	—
RS-485	✓
Default IP address	DHCP / 192.168.1.88
Default admin user / password	admin / 12345
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH10-2WIRE-TX 	—
Web browser access ports	7080
PC client access ports	7080
Main features	Range : ~ 10 cm ,	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Operation modes - Set with jumpers 	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 1024 x 600 px • Day/Night mode (color/b&w/auto) • RESET button • Wiegand 26 • Relay output operating modes: access control or notification of an exception
Color	Silver
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)
Power supply	12 V DC	ETH10-2WIRE-TX : <ul style="list-style-type: none"> • 30 ... 56 V DC - PoE • 10 ... 56 V DC - Power ETH10-2WIRE-RX : <ul style="list-style-type: none"> • 10 ... 56 V - Power • The output PoE voltage is equal to the input voltage 	PoE (802.3af/at)
Power consumption	≤ 12 W	1.35 W (total)	0.3 W
Housing	Compact - Metal	Plastic (PC)	Plastic
"Index of Protection"	IP66	IP20	...
Length of the cable	64 cm
Operation temp	-25 °C ... 65 °C	...
Weight	0.006 kg	0.32 kg	0.76 kg	0.03 kg (single element)	0.05 kg
Dimensions	86 x 54 x 0.8 mm	600 x 35 x 35 mm	112 x 220 x 41 mm (with bracket)	51 x 51 x 24 mm (single element)	88 x 44 x 22 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	ATLO	...	APTI	ATTE	...
Guarantee	2 years	2 years	3 years	3 years	2 years