




	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR XVR5816S-I3 WizSense 16 CHANNELS DAHUA	NVR APTI-N3212AI-I3 32 CHANNELS
		
	1699.17 CAD 1699.17 CAD	312.64 CAD 312.64 CAD
Supported resolutions	...	max. 12 Mpx - 4000 x 3000 px
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	TCP/IP
Video inputs	16 pcs BNC	...
Video outputs	2 pcs HDMI 1 pcs VGA	1 pcs HDMI 4K 1 pcs VGA
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard
Audio inputs	1 pcs - BNC socket - Microphone 16 pcs - BNC socket 16 - Audio support via coaxial cable, HD-CVI only	1 pcs CINCH
Bitrate	...	320 Mbps
Audio outputs	1 pcs BNC socket	1 pcs CINCH
Image compression method	AI Coding / H.265+ / H.265 / H.264+ / H.264	H.265+ / H.265 / H.264+ / H.264
Network interface	...	1 x RJ-45 10/100/1000 Base-TX
Network protocols	...	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE
ONVIF	...	✓
Default IP address	...	192.168.1.88
Default admin user / password	...	admin / 12345
Web browser access ports	...	80, 5000, 554
PC client access ports	...	80, 5000, 554

Image records resolutions	<p>AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1440 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 ,</p> <p>AHD / HD-TVI : 3M-N 1024 x 1536 ,</p> <p>CVBS : 960H - 960 x 576</p> <p>IP : max. 8.3 Mpx 4K UHD - 3840 x 2160</p>	...
Serial ports	...	—
Intelligent image analysis	...	✓
Power consumption	...	≤ 15 W (without HDD)
Recording speed adjustment	8.3 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 10 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation temp	...	-10 °C ... 50 °C
Operation modes	16 x AHD / HD-CVI / HD-TVI / CVBS / IP + 8 x IP	...
Recording modes	Manual, Motion Detection, Schedule	Manual, Sensor, Motion detection, Schedule
Supported hard drives	<ul style="list-style-type: none"> • 8 x 16 TB SATA • 1 x Port eSATA 	2 x 10 TB SATA
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive	Records backup at (.avi) format to USB (pendrive)

Searching and playback the records	<p>Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)</p> <p>Intelligent face search AI - simultaneous search in the archive of face recordings based on max 8 photos taking into account the similarity threshold (for each photo separately) 1/4/9/16 channel synchronous playback</p>	<p>Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p</p>
Network functions	<p>Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users</p>	<p>Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters</p>
Mobile phones support	<p>Port no.: 37777 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS <p>See how to configure the P2P function in Dahua recorders and how to enable the mobile application</p>	<p>Access by a cloud (P2P)</p> <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • Android: Free application BitVision, iOS: Free application iVMS320
Alarm inputs / outputs	16 / 6	4 / 1
PTZ control	<p>IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P</p>	IP Speed Dome Cameras
Motion Detection	Split the screen into zones	Split the screen into zones : 22 x 18 motion zones

Main features	<ul style="list-style-type: none"> • Cooperation with Dahua devices working in the concept of the Internet of Things (IoT), • POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, • SMD PLUS - searching for an object classified as: human, motor vehicle • Coax Audio/Alarm support, • Intelligent image analysis : crossing the line (tripwire), intrusion, classification of people and vehicles • advanced face recognition and search functions • Support for up to 10 face databases, including 10 000 face images • Detection of faces not included in the device database • Searching for faces in recordings based on max 8 selected photos with the ability to independently set the similarity threshold for each photo • RS-232 interface 	<ul style="list-style-type: none"> • Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom
USB	2 pcs USB 2.0 2 pcs USB 3.0	<ul style="list-style-type: none"> • 1 pcs USB 2.0 • 1 pcs USB 3.0
Mouse support	✓	✓
IR remote controller in the set	—	—
Power supply	230 V AC	12 V / 4 A (power adapter included)
Color	Black	...
Weight	6.7 kg	2.71 kg
Dimensions	440 x 463 x 95 mm	380 x 323 x 51 mm
Supported languages	Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian	Polish, English, French, Spanish, German, Portuguese, Russian, Ukrainian, Italian
Country of origin	China	...

Manufacturer / Brand	DAHUA	APTI
Guarantee	5 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00