

	POWER DISTRIBUTION UNIT ACAR-P7 (5 + 2 OUTLETS)	HANGING RACK CABINET DOUBLE-SECTION EPRADO-R19-9U/550/2S	SWITCH POE GTX-B1-10-82G 8-PORT	INDUSTRIAL POE SWITCH TSW202 8-PORT SFP Teltonika
				
	17.46 USD 17.46 USD	132.49 USD 132.49 USD	76.84 USD 76.84 USD	129.48 USD 129.48 USD
Internal width	...	19 "
Internal height	...	9 U
Rated voltage	230 V AC / 50 Hz
Internal depth	...	320 mm
Total maximal current	10 A
External width	...	600 mm
Maximal total load	2300 W
External height	...	500 mm
Response time	< 25 ns
External depth	...	550 mm
Number of outlets	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V
Holes for fan coolers	...	105 x 105 mm (2 places)
LAN ports	• 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink	• 8 x RJ45 (8 x PoE+ (802.3af/at)), • 2 x SFP (Uplink)
Automatic delayed fuse	10 A / 250 V
Bearing capacity	...	30 kg
Leak current	< 0.5 mA
Color	...	Black, RAL9004
Nominal voltage of surge suppressor	250 V / 50 Hz
Protection level of surge suppressor	≤ 1.3 kV (L/N)
Door	...	• Front: glass • Rear: metal, hinges • Front door can be installed as left side or right side one
Nominal stroke current	2 kA (L/N) - (8/20μs)
Management	—	✓
Switch	two-way, with light indication
Maximum stroke current	6.5 kA (L/N) - (8/20μs)
Length of the cable	1.45 m
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act, Speed	Power, Link/Act, SFP, AUX

Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink, • 10 / 100 Mbps : 8 x Port LAN & PoE 	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 1000 Mbps - 2 SFP (Uplink) ports
Default IP address	192.168.1.2
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports 	30 W / port PoE - 1 ... 8 ports
Maximal total power	120 W	240 W
MAC addresses table	2k	8k
Protections	Overvoltage \pm 4 kV	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	<ul style="list-style-type: none"> • Cable entries are placed from the top and bottom • Cable entries broken off : 2 pcs 115 x 45 mm - from the top • 2 pcs 115 x 45 mm - from the bottom • 4 keys included • 4 pcs Rack rails to mounting the devices 	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (Teltonika RMS application), • Compliance with the EtherNet/IP, PROFINET, SNMP V2,V3, LLDP protocol • QoS - 802.1p/DSCP traffic priority • IEEE 802.1x and Radius Authentication • IEEE802.1Q VLAN support • Loop Protection • Spanning Tree STP/RSTP • DHCP client/server support • Port mirroring function, Port Isolation • Static routing • IPv6 compliance • Queue scheduling: SP, WFQ, WRR • Storm Control function • Cable test • Intelligent PoE power management - the device controls power consumption on individual ports • PoE Port Restart • Remote update of software • WitchOS (Linux OS based) system • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Durable aluminum housing • Shock-proof • Industrial wide temperature design. • Mounting on DIN rail, • 2-pin industrial power socket, • Wide range of supported supply voltages • Grounding • "Index of Protection" : IP30 • RESET button
Certificates	CE, FCC Class B	CE, UKCA, FCC, RoHS, WEEE
Housing	Plastic - non-flammable	Aluminum
Power supply	100 ... 265 V AC	• 7 ... 57 V DC (power adapter not included) ,
Power consumption	• ≤ 8 W • PoE : ≤ 248 W
Operation temp	-10 °C ... 45 °C	-40 °C ... 75 °C
Weight	0.44 kg	21.1 kg	0.77 kg	0.6 kg
Dimensions	370 x 65 x 44 mm	...	210 x 150 x 35 mm	132 x 44 x 122 mm
Manufacturer / Brand	...	EPRADO	...	Teltonika

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	2 years	2 years	2 years	2 years
-----------	---------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00