



	SWITCH POE S4100-4GT2GT-60-C 4-PORT DAHUA	IP SPEED DOME CAMERA OUTDOOR OMEGA-51P18-8P - 5 Mpx 5.35 ... 96.3 mm
		
	1689.45 SEK 1689.45 SEK	2873.70 SEK 2873.70 SEK
Standard	...	TCP/IP
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	5 Mpx
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 10/100/1000 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink 	...
Resolution	...	2592 x 1944 - 5 Mpx , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports 	...
Lens	...	5.35 ... 96.3 mm
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports 	...
Maximal total power	60 W	...
View angle	...	<ul style="list-style-type: none"> • 59 ° ... 3.6 ° (manufacturer data) • 48 ° ... 3.7 ° (our tests result)
MAC addresses table	2k	...
Optical zoom	...	x 18
Management	✓	...
Auto IR illuminator	...	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions
Range of IR illumination	...	80 m
Video output	...	—
Operation modes	Long Distance PoE On : 250 m, 10 Mbps @ UTP cat. 5e, 6	...
Rotation speed (manual control)	...	1 °/s ... 80 °/s (horizontal) 1 °/s ... 40 °/s (vertical)

LED diodes	Power, System, Link/Act, PoE	...
Horizontal rotation range	...	360 ° continuous
Vertical rotation range	...	0 ° ... 93 °
RS-485 interface	...	—
Number of presets	...	255
Horizontal scan	...	✓
Image compression method	...	H.265 / H.264
Alarm inputs / outputs	...	—
Network interface	...	10/100 Base-T (RJ-45)
Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Compliance with the LLDP protocol • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall 	...
Certificates	CE	...
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	Overvoltage
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
Main stream frame rate	...	<ul style="list-style-type: none"> • 20 fps @ 5 Mpx • 25 fps @ 4 Mpx
WEB Server	...	Built-in
ONVIF	...	✓

Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / admin The administrator password should be set at the first start
Web browser access ports	...	80
Port ONVIF	...	8999
RTSP URL	...	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream
Route settings	...	8
OSD menu	...	preset 95
Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection, video tampering • ROI - improve the quality of selected parts of image • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • Auto White Balance • IR illuminator optimization • Mirror - Mirror image • Privacy zones - max. 4
Power supply	53 V DC / 1.22 A (power adapter included)	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 3 A (power adapter included)
Power consumption	≤ 60 W	≤ 33 W
Housing	Desktop, Metal	Speed Dome, Metal
Color	...	White + Black
"Index of Protection"	...	IP66
Operation temp	-10 °C ... 55 °C	-20 °C ... 60 °C
Weight	0.31 kg	1.5 kg (with bracket)

Dimensions	130 x 90 x 26 mm	200 x 269 x 137 mm (with bracket)
Supported languages	...	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	DAHUA	OMEGA
Guarantee	3 years	2 years