



	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC- HFW1200T-0280B-S6 - 1080p 2.8 mm DAHUA	EXTENDER EXT-POE2H IN A HERMETIC CASING PULSAR
		
	58.16 EUR 58.16 EUR	67.61 EUR 67.61 EUR
Standards	...	PoE : IEEE 802.3at, IEEE 802.3af
Standard	AHD, HD-CVI, HD-TVI, PAL	...
Input voltage	...	42 ... 57 V DC
Sensor	Progressive Scan CMOS	...
Output voltage	...	42 ... 57 V DC
Matrix size	2.1 Mpx	...
Number of inputs	...	1
Number of outputs	...	2
Connector	...	3 x RJ-45 socket
LED indicators	...	LAN, PoE
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	...
Lens	2.8 mm	...
View angle	• 101 ° (manufacturer data) • 104 ° (our tests result)	...
Range of IR illumination	30 m	...
IR illuminator power adjustment	Automatic	...
Supported data rates	...	• Range : 100 m - Input, 100 m - 2 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet
Output power	...	15.4 W / Port PoE OUT 1/2 , max. 20 W (total)
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	...
OSD menu	✓	...
Protections	...	• Overvoltage • Overload • Short-circuit
Operation temp. / Relative humidity	...	-10 ... 40 °C / 10 ... 90 %

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Privacy zones - max. 8 • Sharpness - sharper image outlines 	...
Power supply	12 V DC / 275 mA	...
Power consumption	≤ 3.3 W	...
Housing	Compact, Metal	Plastic, hermetic
Color	White	...
"Index of Protection"	IP67	IP56
Operation temp	-40 °C ... 60 °C	...
Weight	0.34 kg	0.55 kg
Dimensions	175 x 71 x 72 mm	198 x 148 x 78 mm
Manufacturer / Brand	DAHUA	PULSAR
Guarantee	3 years	2 years