




	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE19D0T-VPIT3F(2.7-13.5MM)(C) - 1080p 2.7 ... 13.5 mm Hikvision	LOW RESISTANCE METER UT-620A UNI-T	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE57H0T-VPITF(2.8mm)(C) - 5 Mpx Hikvision
			
	102.32 EUR 102.32 EUR	577.21 EUR 577.21 EUR	87.39 EUR 87.39 EUR
Standard	AHD / HD-CVI / HD-TVI / PAL	...	AHD / HD-CVI / HD-TVI / CVBS
Sensor	Progressive Scan CMOS	...	Progressive Scan CMOS
Matrix size	2 Mpx	...	5 Mpx
Resolution	<ul style="list-style-type: none"> • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps • 960 x 576 - 960H @ PAL 	...	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL
Resistance measurement	...	120 mΩ ± (0.25% + 25) @ 0.01 mΩ , 600 mΩ ± (0.25% + 25) @ 0.01 mΩ , 6 Ω ± (0.25% + 25) @ 0.0001 Ω , 60 Ω ± (0.25% + 25) @ 0.001 Ω , 600 Ω ± (0.25% + 25) @ 0.01 Ω , 6 kΩ ± (0.75% + 30) @ 0.0001 kΩ	...
Automatic change of measuring ranges	...	—	...
RS-232	...	—	...
Lens	2.7 ... 13.5 mm	...	2.8 mm
USB	...	✓	...
View angle	100 ° ... 30 °	...	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 79 ° (our tests result)
IR illuminator support	ICR - Movable InfraRed filter
Range of IR illumination	40 m	...	20 m
IR illuminator power adjustment	Automatic	...	Automatic
Audio	—

Main features	...	<ul style="list-style-type: none"> • Hold - stopping the meter reading, • 4-lead measurement, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case 	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines 	...	<ul style="list-style-type: none"> • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • D-WDR - Wide Dynamic Range • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	✓
Power supply	• 12 V DC ± 15 % / 420 mA	Built-in 7.4V / 4000mAh battery, 9V / 4A power adapter included	12 V DC / 340 mA
Power consumption	≤ 5 W	...	≤ 4.3 W
Housing	Compact, Metal + Plastic	...	Dome, Metal
"Index of Protection"	IP67	...	IP67
Vandal-proof	IK10
Color	White	...	White
Operation temp	-40 °C ... 60 °C	...	-40 °C ... 60 °C
Weight	0.57 kg	1.33 kg	0.37 kg
Dimensions	255 x 85 x 92 mm	269 x 182 x 60 mm	Ø 111 x 85 mm
Manufacturer / Brand	Hikvision	UNI-T	Hikvision
SAP Code	300513634	...	300613629
Guarantee	3 years	2 years	3 years