





	<a href="#">RFID PROXIMITY CARD WITH MODIFIED UID EMC-4</a>	<a href="#">RUBBER MAT MB-GUM/50</a>	<a href="#">KIT ZSW-01 SUPLA ZAMEL</a>	<a href="#">ELECTRIC CABLE DY-2.5-BK/750V</a>
				
	3.44 EUR 3.44 EUR	6.31 EUR 6.31 EUR	423.25 EUR 423.25 EUR	0.44 EUR 0.44 EUR
Standard	Unique EM 125kHz	...	...	...
Compatibility	EM4100/4102	...	...	...
Possibility of programming the serial number (ID)	✓	...	...	...
Support	...	...	SUPLA	...
Ability to write to internal memory	—	...	...	...
In section	...	...	...	<b>100 m . Price for 1m when buying a whole roll</b>
Serial Number overprint	—	...	...	...
Inner conductor	...	...	...	2.5 mm <sup>2</sup> - Cu wire
Material	...	SBR granulate + polyurethane binder	...	...
Rated voltage	...	...	...	450 / 750 V
Wireless	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Outer coating	...	...	...	Ø 3.3 mm - PVC
Mobile phones support	...	...	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	...
Coating color	...	...	...	Black
Main features	Can be programmed using the RUD-1 + PRT-32EM	<ul style="list-style-type: none"> <li>• Rough structure</li> <li>• Granule fraction : 0.5 ... 4 mm</li> <li>• Insulation</li> <li>• High fatigue strength of the material</li> <li>• Weatherproof</li> <li>• Very easy and quick assembly</li> </ul>	<ul style="list-style-type: none"> <li>• Control from a Web browser,</li> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Possibility to manually program scenarios from the built-in API</li> </ul>	...
Housing	...	...	Plastic	...
Color	...	Black	Green	...
Guarantee	2 years	...	2 years	2 years
Manufacturer / Brand	ROGER	...	ZAMEL	...
Maximal outputs load	...	...	350 W	...
Number of elements	...	...	7 6 1	...

Application	...	<ul style="list-style-type: none"> <li>• Area covering,</li> <li>• Soundproofing</li> </ul>	roller shutters, roof windows, awnings, drop-down screens, curtains swing gates, sliding gates, garage gates, doors	...
Power voltage	...	...	230 V AC 24 V AC/DC	...
Relay maximal load	...	...	2 x 5 A @ 250 V AC 5 A @ 250 V AC	...
Number of inputs	...	...	2 pcs 2	...
Number of outputs	...	...	1 pcs ( Motor ) 1	...
Connector type	...	...	screw terminals screw terminals screw terminals	...
"Index of Protection"	...	...	IP20 IP20	...
Operation temp	...	...	-10 °C ... 55 °C -20 °C ... 50 °C	...
Weight	0.006 kg	2.4 kg	0.410 kg 0.030 kg 0.034 kg	...
Dimensions	86 x 55 x 1 mm	500 x 500 x 10 mm	47 x 47 x 20 mm 47 x 47 x 20 mm	...