

	IP CAMERA IPC-HFW3849T1-AS-PV-0280B-S5 TiOC Full-Color - 8.3 Mpx 4K UHD 2.8 mm DAHUA	POWER DISTRIBUTION UNIT AK-SP-05U (5 OUTLETS + 2 USB) AKYGA	OUTDOOR SIDE OPENING HOUSING DH-PFH610N-IR-W DAHUA
			
	197884.62 HUF 197884.62 HUF	5703.85 HUF 5703.85 HUF	115865.38 HUF 115865.38 HUF
Standard	IP
Rated voltage	...	230 V AC / 50 Hz	...
Total maximal current	...	10 A	...
External dimensions	404 x 164 x 175 mm
Maximal total load	...	2500 W	...
Response time	...	< 25 ns	...
Internal dimensions	255 x 90 x 83 mm
Glass dimensions	Ø 50 mm
Number of outlets	...	• 5 grounded outlets 10A/250V, • 2 USB ports 2A/5V	...
Material	Aluminum - powder painted / PC
Automatic delayed fuse	...	10 A / 250 V	...
Thermostat	✓
IR illuminator	100 m
Nominal voltage of surge suppressor	...	250 V / 50 Hz	...
DC filter to eliminate interferences	...	RFI ≤ 10 dB	...
Maximum stroke current	...	4.5 kA	...
Maximum energy absorption	...	150 J	...
Switch	...	with light indication	...
Main features	• The product is adapted to work outdoors (heater and fan cooler built-in) • Wiper • Bracket not included in the kit
Length of the cable	...	1.5 m	...
Operation temp	...	5 °C ... 50 °C	-40 °C ... 60 °C
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	1/2.8 " Progressive Scan CMOS
Lens	2.8 mm
View angle	106 °
Range of IR illumination	30 m
White light LED illuminator range	30 m

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Min. illumination	0.004 Lux / F1.0 (color)
S/N ratio	> 56 dB
RS-485 interface	—
Memory card slot	Micro SD card support up to 256GB
Image compression method	AI H.265 / H.265+ / H.265 / AI H.264 / H.264+ / H.264
Alarm inputs / outputs	1 / 1
Audio	<ul style="list-style-type: none"> • Microphone built-in - 2 pcs, • External microphone input, • Speaker built-in • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	25 fps @ 8.3 Mpx
Network interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	20
ONVIF	✓
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Intelligent image analysis	<ul style="list-style-type: none"> • intrusion - classification of people and vehicles • crossing the line (tripwire) - classification of people and vehicles • video tampering • scene changing • classification of people and vehicles



Main features	<ul style="list-style-type: none"> • Active deterrence function, Alternately flashing LEDs: red and blue - frequency configuration, Siren sound - 3 volume levels • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles • SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms • AI SSA AI Smart Scene Adaptive - scene auto-adaptation using deep learning algorithms to detect environmental conditions such as rain, fog, backlight, low light and flickering, in order to set the optimal image parameters • AcuPick support - technology that uses artificial intelligence on both front-end and back-end to search through massive amounts of video data to quickly locate targets with high precision • BLC/HLC - Back Light / High Light Compensation • Day/night mode • Full Color - colorful night mode • Auto White Balance • AGC - Automatic Gain Control • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Image rotation and mirror • Light and sound alarm • White light (LED) illuminator built-in : 2 LEDs
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 630 mA 	...	24 V AC / 5 A
Power consumption	<ul style="list-style-type: none"> • ≤ 9.4 W @ PoE • ≤ 7.7 W @ 12 V
Housing	Compact - Metal	Plastic (ABS)	...
Color	White + Black	Black	...
"Index of Protection"	IP67	...	IP66
Mechanical protection class	—
Operation temp	-40 °C ... 60 °C
Weight	1 kg	0.318 kg	2.78 kg
Dimensions	289 x 95 x 85 mm	305 x 50 x 40 mm	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian
Manufacturer / Brand	DAHUA	AKYGA	DAHUA
Guarantee	3 years	2 years	3 years